



WRGU-10MTT-C-2-6A, Self reclosing

Code: P21810. DESCATALOGADO

> Poles: 2 > In (A): 6 A

> Breaking element: built-in

> Curve: C

Description

The WRGU-10 MTT compact assembly forms a self-reclosing circuit breaker (overload and short-circuit) and residual current protection system in single-phase or threephase electrical installations with a neutral of up to 63 A. The assembly is composed of the following elements:

- o Residual current relay for protection, with **RGU-10 MTT** self-reclosing function
- o MP-T series motorized circuit breaker as an overload and short-circuit protection element, and as a circuit breaker in residual current protection
- o WGC residual current transformer, residual current sensor for residual current protection
- o Remote switch, for resets and external manual reclosures

Application

The WRGU-10 MTT groups can be used to make safety compatible with the continuity of the service in remote installations or installations with more complicated maintenance. They ensure residual current (mandatory) and circuit breaker protection, guaranteeing selfreclosing for either of the two reasons. It is a very good solution in installations in special locations that are hard to control and monitor: telephony installations, television repeaters, refrigerating chambers, etc.

- Telephony systems
- o DTT systems
- o Industrial refrigerating chambers







Complete protection and reclosing unit Residual current and circuit breaker

Code: P21810.

Specifications

AC power supply	
Consumption	6 VA
Frequency	50 Hz
auxiliary power supply mode	230 V ~
Nominal voltage	230 V ~ (± 20 %)
Mechanical characteristics	
Size (mm) width x height x depth	225 x 205 x 110 (mm)
Envelope	Colour box RAL 7035
Environmental characteristics	
Storage temperature	Circuit breaker: −55 +55 °C
Working temperature	Circuit breaker and relay: -25 +55 °C / Motor reconnection: -25 +70 °C
External reset input for tripping	
Туре	ON-OFF Remote
Motor	
On / off pulse time	Opening time: < 10 ms / Closing time: < 1000 ms
Nominal voltage	230 / 380 V ~
Standards	
Standards	IEC 60947-2, IEC 60755, UNE-EN 55022, UNE-EN 55011, UNE-EN 55024 level 4, IEC 61000-4-11
Digital relay outputs	
Nominal load in AC	2500 VA
Nominal current	5 A ~
Maximum current	10 A ~
Electrical life	Magnetotérmico: 10000 maniobras / Motor reconexión: >20000
Mechanical life	Magnetotérmico: >20000 operations
Measurement accuracy	
Phase current measurement	± 20 %
Differential protection	
Туре	Type A ultra-immunised
Sensitivity (I∆n), A	0,03-0,1-0,3-0,5 (Setup)
Delay time (tΔ)	Curve INS / SEL







Complete protection and reclosing unit Residual current and circuit breaker

Code: P21810.

Protection

Reset time

Reclosure time

240 / 415 V ~
10 kA (IEC 60898)
6
C ó D (según modelo)
Motorised circuit breaker MP-T series
True root mean square (TRMS)
Voltage presence Earth leakage tripping Reclosure timing

Certified and Approved by Telefónica Residual current relay with adjustable sensitivity (0.03 A, up to 0.5 A), adjustable delay (with curve, INS/SEL, or by time, from 0.1 to 1 s) and automatic reclosing system, 15 attempts by default (residual current) and 2 by the circuit breaker

Diff & Magneto: 15 min

Differential: 20 s, 40 s, rest 3 min / Circuit breaker: 3 min







Complete protection and reclosing unit Residual current and circuit breaker

Code: P21810.

Dimensions







