



REC3-2P-40-300T

REC3-2P-40-300T

Code: P26123. (CONSULTAR DISPONIBILIDAD)

- > RCCB self-reclosing
- > In (A): 40 A
- > Reclosing mode: Time
- > Poles: 2
- > Sensitivity: 300 mA

Specifications

AC power supply

Installation category	CAT III 300 V
Consumption	5 VA
Frequency	50/60 Hz ($\pm 5\%$)
Nominal voltage	230 V ~ ($\pm 15\%$)

Mechanical characteristics

Size (mm) width x height x depth	79.5 x 120 x 82 (mm)
Envelope	Plastic V0 polycarbonate
Cable gauge at power supply terminals	16-25 mm ²
Cable gauge at voltage terminals	16-25 mm ²
Fastening	DIN rail
Weight (kg)	0,62

Environmental characteristics

Protection class	IP 20
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-35 ... +65 °C
Working temperature	-25 ... +55 °C

Measurement circuit

Defect resistance (Rd) / Differential response	< 15 k Ω / Do not self-reclosing
Accepted minimum resistance (Rd0) / Differential response	> 5 k Ω / Self-reclosing

Standards

Electrical safety, Maximum height (m)	2000
Standards	UNE-EN 61008-1, UNE-EN 50557

User interface

LED	2 LED: AUTO, color green / REC, color red
-----	---

Circuit breaker / RCCB

Rated conditional short-circuit current (Inc)	10 kA to 230/400V with gB 80A fuse
Nominal current (In)	40 A



REC3-2P-40-300T

Self-reclosing RCCB

Code: P26123.

Assigned frequency (Hz)	50/60
Rated breaking and re-closure capacity (Im)	500 A
Shock wave resistance	Class A, AC: 250A 8/20µs Class S: 3000A 8/20µs
Rated nominal voltage (Un)	230 V ~

Differential protection

Type	Type A
Sensitivity (IΔn), A	0,3
Delay time (tΔ)	INS

Protection

Circuit breaker type	Circuit breaker / RCCB
----------------------	------------------------

Reclosure type

Reclosure number	3
Reclosure time	3/20/180 s