



REC4-2P-40-300

REC4-2P-40-300, RCCB with self-reclosing system, type A

Code: P26A23.

> Poles: 2 > In (A): 40 A

> Reclosing mode: Time> Sensitivity: 300 mA> Breaking element: built-in> Type of protection: Type A

Specifications

Installation category	CAT III 300 V		
Consumption	5 VA		
Frequency	50/60 Hz (± 5 %)		
Nominal voltage	230 V ~ (± 20 %)		
Mechanical characteristics			
Size (mm) width x height x depth	54.5 x 115.5 x 81 (mm)		
Envelope	Plastic VO polycarbonate		
Fastening	DIN rail		
Weight (kg)	0,28		
invironmental characteristics			
Protection class	IP 20		
Relative humidity (without condensation)	5 95 %		
Storage temperature	-35 +65 ℃		
Working temperature	Earth leakage protection: -25 +55 °C Reclosing: -10 +55 °C		
tandards			
Electrical safety, Maximum height (m)	2000		
Electrical safety, Installation category	CAT III 300 V ~		
Electrical safety, Contamination level/class	Pollution resistance 2		
Standards	UNE-EN 61008-1, UNE-EN 63024		
lser interface			
LED	2 LED: AUTO, color green / REC, color red		
ircuit breaker / RCCB			
Rated conditional short-circuit current (Inc)	10 kA to 230/400V with gB 80A fuse		
Nominal current (In)	40 A		
Assigned frequency (Hz)	50/60		
Rated breaking and re-closure capacity (Im)	500 A		
Shock wave resistance	Class A, AC: 250A 8/20µs Class S: 3000A 8/20µs		







REC4-2P-40-300

Self-reclosing RCCB

Code: P26A23.

Rated nominal voltage (Un) $230 \text{ V} \sim$

Differential protection

Туре	Туре А
Sensitivity (I∆n), A	0,3
Delay time (t∆)	INS

Reclosure type

Reclosure number	3
Reset time	10/20/60 s
Reclosure time	< 3/20/180 s

REC4RCCB with self-reclosing system, type A

CODE	TYPE	Poles	In (A)	Reclosing mode	Breaking element
P26A21.	REC4-2P-40-30	2	40 A	Insulation	built-in
P26A23.	REC4-2P-40-300	2	40 A	Time	built-in
P26A31.	REC4-2P-63-30	2	63 A	Insulation	built-in
P26A33.	REC4-2P-63-300	2	63 A	Time	built-in
P26F21.	REC4-4P-40-30	4	40 A	Time	built-in
P26F23.	REC4-4P-40-300	4	40 A	Time	built-in
P26F31.	REC4-4P-63-30	4	63 A	Time	built-in
P26F33.	REC4-4P-63-300	4	63 A	Time	built-in

3 reconnections: 3, 20, 180 s.







REC4-2P-40-300

Self-reclosing RCCB

Code: P26A23.

Dimensions

Connections





