

# REC4-C 2P 40 30

REC4-C-2P-40-30, RCCB with self-reclosing, 2 poles

Code: P27A21.

> In (A): 40A
> Reclosing mode: Time
> Sensitivity: 30 mA
> Breaking element: built-in
> Type of protection: Type A

## Description

Description
The **REC4** is a family of 2- or 4-pole RCCBs linked to a smart reclosing motor, which makes it possible to safely reclose the corresponding RCCB. The **REC4-C** version offers the option of signalling that the maximum number of reconnections has been reached by means of a status output.
Compact device that is installed as an RCCB. There is no need to interconnect the motor and the RCCB.
The reconnection system is time-based. The device has a locking system to control operation in manual or automatic mode (reclosing enabled).

## Application

All electrical installations needing a full, continuous power supply faced with unforeseen incidents not caused by electric insulation which cause the RCCB to trip.

- Housing sector: refrigerators, alarms, garage doors
- Services sector: air conditioning, cold storage rooms, lighting, UPS, etc.
- Industry sector: control of critical production processes



# REC4-C 2P 40 30

Self-reclosing RCCB type A

Code: P27A21.

## Specifications

### AC power supply

| | |
|---|---|
| Installation category | CAT III 300 V |
| Consumption | 6 VA |
| Frequency | 50/60 Hz (± 5 %) |
| Nominal voltage | 230 V ~ (± 20 %) |

### Mechanical characteristics

| | |
|---|---|
| Size (mm) width x height x depth | 54.5 x 112 x 81 (mm) |
| Envelope | Plastic V0 polycarbonate |
| Fastening | DIN rail |
| Weight (kg) | 0,3 |

### Environmental characteristics

| | |
|---|---|
| Protection class | IP 20 / IK 08 |
| Relative humidity (without condensation) | 5 ... 95 % |
| Storage temperature | -35 ... +65 °C |
| Working temperature | Earth leakage protection: -25 ... +55 °C Reclosing: -10 ... +55 °C |

### Standards

| | |
|---|---|
| Electrical safety, Maximum height (m) | 2000 |
| Electrical safety, Installation category | CAT III 300 V ~ |
| Electrical safety, Contamination level/class | Pollution resistance 2 |
| Standards | UNE-EN 61008-1, UNE-EN 63024 |

### User interface

| | |
|---|---|
| LED | 2 LED: AUTO, color green / REC, color red |

### Circuit breaker / RCCB

| | |
|---|---|
| Rated conditional short-circuit current (Inc) | 10 kA to 230/400V with gB 80A fuse |
| Nominal current (In) | 40 A |
| Assigned frequency (Hz) | 50/60 |
| Rated breaking and re-closure capacity (Im) | 500 A |
| Shock wave resistance | Class A, AC: 250A 8/20µs Class S: 3000A 8/20µs |
| Rated nominal voltage (Un) | 230 V ~ |

### Differential protection

| | |
|---|---|
| Sensitivity (IΔn), A | 0,03 |
| Delay time (tΔ) | INS |

Creation date: 23/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



# REC4-C 2P 40 30

Self-reclosing RCCB type A

Code: P27A21.

## Protection

| | |
|---|---|
| Safety relay type (class) | Class A ( IEC 61008.1) |
| Circuit breaker type | Circuit breaker / RCCB |

## Reclosure type

| | |
|---|---|
| Reclosure number | 3 |
| Reset time | 10/20/60 s |
| Reclosure time | 3/20/180 s |

**REC4-C**
RCCB with self-reclosing system, type A with status output

| CODE | TYPE | Poles | In (A) | Reclosing mode | Sensitivity | Type of protection |
|---|---|---|---|---|---|---|
| P27A21. | REC4-C 2P 40 30 | 2 | 40A | Time | 30 mA | Type A |
| P27A31. | REC4-C 2P 40 300 | 2 | 40A | Time | 300 mA | Type A |
| P27A23. | REC4-C 2P 63 30 | 2 | 63 A | Time | 30 mA | Type A |
| P27A33. | REC4-C 2P 63 300 | 2 | 63 A | Time | 300 mA | Type A |
| P27F21. | REC4-C 4P 40 30 | 4 | 40A | Time | 30 mA | Type A |
| P27F31. | REC4-C 4P 40 300 | 4 | 40A | Time | 300 mA | Type A |
| P27F23. | REC4-C 4P 63 30 | 4 | 63 A | Time | 30 mA | Type A |
| P27F33. | REC4-C 4P 63 300 | 4 | 63 A | Time | 300 mA | Type A |

3 reconnections: 3, 20, 180 s. Consult reference for different modes of operation of the status output.



Creation date: 23/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.





# REC4-C 2P 40 30

Self-reclosing RCCB type A


Code: P27A21.

## Dimensions




## Connections






Creation date: 23/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.