



REC4-C-4P-63-30, RCCB with self-reclosing, 4 poles

Code: P27F23.

> In (A): 63 A

> Reclosing mode: Time > Sensitivity: 30 mA > Breaking element: built-in

> Type of protection: Type A

Description

Description

The **REC4** is a family of 2- or 4-pole RCCBs linked to a smart reclosing motor, which makes it possible to safely reclose the corresponding RCCB. The **REC4-C** version offers the option of signalling that the maximum number of reconnections has been reached by means of a status output.

Compact device that is installed as an RCCB. There is no need to interconnect the motor and the RCCB.

The reconnection system is time-based. The device has a locking system to control operation in manual or automatic mode (reclosing enabled).

Application

All electrical installations needing a full, continuous power supply faced with unforeseen incidents not caused by electric insulation which cause the RCCB to trip.

O Housing sector: refrigerators, alarms, garage doors

o Services sector: air conditioning, cold storage rooms, lighting, UPS, etc.

o Industry sector: control of critical production processes







Self-reclosing RCCB type A

Code: P27F23.

Specifications

AC power supply	
Installation category	CAT III 300 V
Consumption	6 VA
Frequency	50/60 Hz (± 5 %)
Nominal voltage	230 V ~ (± 20 %)
Mechanical characteristics	
Size (mm) width x height x depth	90.5 x 112 x 81 (mm)
Envelope	Plastic VO polycarbonate
Fastening	DIN rail
Weight (kg)	0,4
Environmental characteristics	
Protection class	IP 20 / IK 08
Relative humidity (without condensation)	5 95 %
Storage temperature	-35 +65 °C
Working temperature	Earth leakage protection: -25 +55 °C Reclosing: -10 +55 °C
Standards	
Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V ~
Electrical safety, Contamination level/class	Pollution resistance 2
Standards	UNE-EN 61008-1, UNE-EN 63024
User interface	
LED	2 LED: AUTO, color green / REC, color red
Circuit breaker / RCCB	
Rated conditional short-circuit current (Inc)	10 kA to 230/400V with gB 80A fuse
Nominal current (In)	63 A
Assigned frequency (Hz)	50/60
Rated breaking and re-closure capacity (Im)	500 A
Shock wave resistance	Class A, AC: 250A 8/20µs Class S: 3000A 8/20µs
Rated nominal voltage (Un)	400 V ~
Differential protection	
Sensitivity (IΔn), A	0,03
Delay time (tΔ)	INS







Self-reclosing RCCB type A

Code: P27F23.

Protection

Safety relay type (class)	Class A (IEC 61008.1)
Circuit breaker type	Circuit breaker / RCCB
Reclosure type	
Reclosure number	3
Reset time	10/20/60 s
Reclosure time	3/20/180 s

RCCB with self-reclosing system, type A with status output $% \left(1\right) =\left(1\right) \left(1\right) \left$

CODE	TYPE	Poles	In (A)	Reclosing mode	Sensitivity	Type of protection
P27A21.	REC4-C 2P 40 30	2	40A	Time	30 mA	Type A
P27A31.	REC4-C 2P 40 300	2	40A	Time	300 mA	Туре А
P27A23.	REC4-C 2P 63 30	2	63 A	Time	30 mA	Туре А
P27A33.	REC4-C 2P 63 300	2	63 A	Time	300 mA	Туре А
P27F21.	REC4-C 4P 40 30	4	40A	Time	30 mA	Туре А
P27F31.	REC4-C 4P 40 300	4	40A	Time	300 mA	Туре А
P27F23.	REC4-C 4P 63 30	4	63 A	Time	30 mA	Туре А
P27F33.	REC4-C 4P 63 300	4	63 A	Time	300 mA	Туре А

3 reconnections: 3, 20, 180 s. Consult reference for different modes of operation of the status output.







Self-reclosing RCCB type A

Code: P27F23.

Dimensions Connections





