



## RECmax P-D2-25

RECmax P-D2-25, Motorized circuit breaker, 2-pole D-curve

Code: P28134. DESCATALOGADO

- > Poles: 2
- > In (A): 25 A
- > Curve: D

### Description

The RECmax P series are 2- and 4-pole circuit breakers connected to a compact motor and internal control unit that enables automatic reclosing.

After triggering, the switch recloses following a sequence of 3 reclosures, with 3 minutes between resets. If the unit is not able to reclose after 3 attempts, it remains triggered until a manual or remote reset is made.

Can also be connected remotely to an external control. It has two inputs which, via voltage-free external signals, order the opening (input O) and subsequent closing (reclosing) of the circuit breaker (input I).

They serve as protection against short-circuits and overloads, and can also be used as a remote circuit breaker. The switch status is indicated by LED signals on the front panel of the unit. A green ON LED indicates that the unit is in service; a red OFF LED indicates that the unit has been tripped. A TEST/RESET of the unit can be performed by pressing a button to check the tripping and subsequent rearming of the unit. It also features two single-contact outputs for signalling the status and the cause of the opening and closing of the circuit breaker (trip, manual/test).

### Application

The RECmax P series are motorized circuit breakers that can be rearmed automatically or controlled remotely, suitable for any application in which remote connection/disconnection control is required.

They are an essential accessory for automatic circuit breaker and residual current reclosing and protection, and for external control of connection/disconnection.



# RECmax P-D2-25

Motorised self-resettable circuit breaker (up to 63 A)

Code: P28134.

## Specifications

### AC power supply

|                       |               |
|-----------------------|---------------|
| Installation category | CAT III 300 V |
| Consumption           | 4,5 VA        |
| Frequency             | 50 / 60 Hz.   |
| Nominal voltage       | 230V ~ ± 30%  |

### Mechanical characteristics

|                                  |                               |
|----------------------------------|-------------------------------|
| Size (mm) width x height x depth | 79 x 110 x 83 (mm)            |
| Envelope                         | Plastic V0 polycarbonate + GF |
| Fastening                        | DIN 46277 (EN 50022)          |
| Weight (kg)                      | 0,425                         |

### Environmental characteristics

|  |   |
|--|---|
| Protection class                         | Motor: IP 40 (DIN 40050) / RECmax MP: IP 20 |
| Relative humidity (without condensation) | 5 ...95 %                                   |
| Working temperature                      | -20 ... +70 °C                              |

### Standards

|                                       |                        |
|---------------------------------------|------------------------|
| Electrical safety, Maximum height (m) | 2000                   |
| Standards                             | IEC 60898, IEC 60947-2 |

### Motor

|                                 |                     |
|---------------------------------|---------------------|
| Frequency (Hz)                  | 50 / 60             |
| Absorbed power                  | 10 VA               |
| Tripping / motor reclosure time | < 10 ms / < 1000 ms |
| On / off pulse time             | > 10 ms / > 10 ms   |
| Maximum voltage                 | 420 V ~             |
| Minimum voltage                 | 90 V ~              |
| Nominal voltage                 | 230 V ~ ± 30 %      |
| Electrical life                 | > 20000 operations  |

### Digital relay outputs

|                 |                 |
|-----------------|-----------------|
| Nominal current | 0,25 A          |
| Type            | Simple contacts |
| Nominal voltage | 230 V           |

### Thermal-magnetic protection

|                        |    |
|------------------------|----|
| Trip curve, Type       | D  |
| Nominal current In (A) | 25 |



# RECmax P-D2-25

Motorised self-resettable circuit breaker (up to 63 A)

Code: P28134.

|   |                 |
|---|-----------------|
| Number of mechanical / electrical manoeuvres  | > 20000 / 10000 |
| Ultimate short-circuit breaking capacity (Icu) / service short-circuit breaking capacity (Ics), in DC (IEC 60947-2) | 30 kA           |
| DC voltage breaking capacity (IEC 60947-2)  | < 125 V         |
| AC ultimate short-circuit breaking capacity (Icu) (IEC 60947-2)   | 20 kA           |
| V~ Breaking capacity (IEC 60947-2)  | 240 V ~         |
| Minimum operating voltage UB min (V)  | 12 V ~          |
| Nominal voltage   | 240 / 415 V ~   |

C/D curve circuit breakers with 6 kA cut off power (IEC 60898).



## RECmax P-D2-25

Motorised self-resettable circuit breaker (up to 63 A)

Code: P28134.

## Dimensions



## Connections

