

## TB-3

### TB-3

Code: P30102. (CONSULTAR DISPONIBILIDAD)

> Programmable power between 15 ... 225 W Control of one circuit (BEACON). Luminosity level controlled by means of a photocell (included with the equipment). 1 alarm relay for failure of circuit or photocell

## Description


The TB-3 type Beacon control system is in charge of the supervision, control and transmission of anomalies detected in the different Beacon components of the telephony transmission towers.

TB-3 Features:

- Start-up control and measurement of the consumption of a single Beacon circuit: group of 1, 2 or 3 75W/230V or 15W/230Vac lamps.
- Inputs for a twilight photocell. The photocell will be supplied with the unit and is connected with the corresponding terminals (+ and - inputs of the photocell).
- Adjustments of the **TB-3**
  - Power of the 15 to 225 W lamp circuit.
  - Light level between 200 and 1000 lux.
- Relay output used to signal alarms.

## Application

Simple unit used to control and supervise a simple Beacon circuit, in addition to the supervision of the photocell's operation.



# TB-3

Beacon control relays

Code: P30102.

## Specifications

AC power supply	
Frequency	50 / 60 Hz
Nominal voltage	230 V~ ±20 %
Mechanical characteristics	
Size (mm) width x height x depth	105 x 90 x 70 (mm)
Weight (kg)	0,99
Environmental characteristics	
Protection class	IP 20
Working temperature	-10 ... +50 °C
Standards	
Standards	IEC 60255-5, UNE 20801-2, UNE 20801-3, UNE 20801-4, UNE-EN 60730-1
Digital relay outputs	
Contact-coil insulation	2500 V~