



GETEST 5...50A

GETEST 5...50A, Indirect earth contact simulator 5 ... 50 A, Smartphone included,

Code: P60123. (DESCATALOGADO)

Specifications

AC power supply

Installation category	CAT II 300 V
Input intensity	15 A ~
Frequency	50 ... 60 Hz
Nominal voltage	230 V ~ ± 20% (L1-N)

Electrical characteristics

Resistance measurement	0 ... 120 Ω
------------------------	-------------

Mechanical characteristics

Size (mm) width x height x depth	285 x 340 x 285 (mm)
Envelope	Steel / Aluminium
Cable gauge at power supply terminals	IEC 60320 C20 16A
Cable gauge at current terminals	4 mm safety banana CAT IV 600 V 32 A
Cable gauge at voltage terminals	4 mm safety banana CAT IV 600 V 32 A
Weight (kg)	45

Environmental characteristics

Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-10 ... +50 °C
Working temperature	0 ... +40 °C

Current measurement circuit

Impedance	< 0.1 Ω
Maximum current	100 A ~
Resolution	Scale: 10 A(0.01 A~) Scale: 100 A (0.1 A ~)

Voltage measurement circuit

Installation category	CAT II 300 V
Input impedance	1 KΩ, 2 KΩ, 10 MΩ
Voltage measuring range	0.8, 30, 70, 105, 280 and 700 V ~ (Self-adjusting)
Maximum value	700 V~

Standards

Electrical safety, Maximum height (m)	2000
Standards	UNE-EN 61010-1, UNE-EN 610110-2-03, UNE-EN 61326-1

Measurement accuracy

Accuracy	2.5 % reading + 2 digits
----------	--------------------------



GETEST 5...50A

Indirect earth contact simulator

Code: P60123.



GETEST 5...50A

Indirect earth contact simulator

Code: P60123.

Dimensions

