



RBE-50-400

RBE-50-400, Reactor

Code: P70245. (CONSULTAR DISPONIBILIDAD)

- > L(mH): 2,29
- > For capacitor: CFB-46/62-6B
- > In (A): 42 A
- > Frequency (Hz): 50
- > kvar (400 V): 50
- > Losses: 185
- > Un (V): 400

Specifications

AC power supply

Frequency	50 Hz
-----------	-------

Electrical characteristic

Overvoltage factor (p %)	7 % (189 Hz)
--------------------------	--------------

Mechanical characteristics

Size (mm) width x height x depth	154 x 233 x 310 (mm)
Envelope	Conductor type: Aluminium strip
Weight (kg)	29

Environmental characteristics

Thermal Class	class F (+155 °C) On request: class H (+180 °C)
Protection class	IP 00
Ambient temperature	-10 ... +45 °C

Electrical characteristics

Linearity (5% L)	1,8 In
Maximum transient current	2 In (1 min)
Voltage	400 V, on request: up to 1000 V
Tolerance L	± 5 %
L value (mH)	2.29
Insulation voltage, circuit	4 kV

Current measurement circuit

Allowable overload	1,17 In
Permanent overload	1,17 In

Standards

Standards	UNE-EN 60289, IEC 60076
-----------	-------------------------

Protection

Circuit breaker type	90°C NC thermostat
----------------------	--------------------



RBE-50-400

Three-phase reactors for static capacitor banks

Code: P70245.
