

# RX-15-400-14%

RX-15-400-14%

Code: P71024.

- > Reactor
- > L(mH): 5,43
- > For capacitor: CLZ-FP-52/25-HD | CFB-52/23
- > Frequency (Hz): 50
- > kvar (400 V): 15

## Specifications

### AC power supply

Frequency	50 Hz
-----------	-------

### Electrical characteristic

Overvoltage factor (p %)	14 % (134 Hz)
--------------------------	---------------

### Environmental characteristics

Thermal Class	class F (+155 °C) On request: class H (+180 °C)
Protection class	IP 00
Ambient temperature	-10 ... +45 °C

### Electrical characteristics

Linearity (5% L)	1,8 x I <sub>n</sub>
Maximum transient current	2 I <sub>n</sub> (1 min)
Voltage	400 V, on request: up to 1000 V
Tolerance L	± 5 %
L value (mH)	5,43
Insulation voltage, circuit	4 kV

### Mechanical characteristics

Envelope	Conductor type: Aluminium strip / copper cable
----------	--

### Current measurement circuit

Allowable overload	1,17 x I <sub>n</sub>
Permanent overload	1,17 x I <sub>n</sub>

### Standards

Standards	UNE-EN 60289, IEC 60076
-----------	-------------------------

### Protection

Circuit breaker type	90°C NC thermostat
----------------------	--------------------