

RBX-25-400-14%

RBX-25-400-14%

Code: P72330.

- > Reactor
- > L(mH): 3,26
- > For capacitor: CLZ-FP-52/12,5-HD + CLZ-FP-52/30-HD | CFB-52/38
- > Frequency (Hz): 50
- > kvar (400 V): 25

Specifications

AC power supply

Frequency	50 Hz
-----------	-------

Electrical characteristic

Overtoltage factor (p %)	14 % (134 Hz)
--------------------------	---------------

Environmental characteristics

Thermal Class	class F (+155 °C) On request: class H (+180 °C)
Protection class	IP 00
Ambient temperature	-10 ... +45 °C

Electrical characteristics

Linearity (5% L)	1,8 x I _n
Maximum transient current	2 I _n (1 min)
Voltage	400 V, on request: up to 1000 V
Tolerance L	± 5 %
L value (mH)	3.26
Insulation voltage, circuit	4 kV

Mechanical characteristics

Envelope	Conductor type: Aluminium strip / copper cable
----------	--

Current measurement circuit

Allowable overload	1,17 x I _n
Permanent overload	1,17 x I _n

Standards

Standards	UNE-EN 60289, IEC 60076
-----------	-------------------------

Protection

Circuit breaker type	90°C NC thermostat
----------------------	--------------------