Page 1 of 4



## **RBZ-20-400**

RBZ-20-400, Reactors III for detuned filters

Code: P73125.

> L(mH): 1,91

Reactors III for detuned filters

> For capacitor: CLZ-FP-46/25

> In (A): 29

> Frequency (Hz): 50 > kvar (400 V): 20

> Losses: 79 > Un (V): 400

#### Description

CIRCUTOR has a complete range of detuned reactors, p = 7%, with a resonance frequency of 189 Hz for 50 Hz networks (or, on demand, 227 Hz for 60 Hz networks). This is the most frequent tuning value to avoid any resonance with the 5th harmonic and over. The set of capacitors-reactors absorbs part of the current of the 5th harmonic and acts as a detuned filter for higher frequencies. In some installations, anyway, other value of p(%) can be required, for example, 8,7 % (170 Hz), 14 % (134 Hz).... CIRCUTOR can manufacture reactors adapted to any power, p (%), frequency, voltage (Un  $\leq$  1000 VAC).

Reactors for low power rating, RZ range, are built with low losses magnetic sheets and coiled with aluminum wires. A terminal block for the connection of the reactor is fitted. Higher powers are covered by RBH range. These reactors are based on a magnetic sheet core with multiple air gaps, which provides them with excellent characteristics and low loss ratios.

Both RZ and RBZ reactors are subjected to a varnish vacuum impregnation, based on polyester resin, to increase the insulation, providing a greater mechanical resistance and reducing the level of noise.

#### **Application**

RZ and RBZ detuned reactors have been specially designed for their use in installations with capacitor banks with considerably high harmonic distortion rates. The reactors must be connected in series to the proper power capacitor for the satisfactory protection of the own capacitors and to avoid the resonance effects in the installation.







# **RBZ-20-400**

Reactors

Code: P73125.

### **Specifications**

AC power supply	
Frequency	50 Hz
Electrical characteristics	
Permanent overload	1,17 x ln
Linearity (5% L)	1,75 x ln
Maximum transient current	2 In (1 min)
Voltage	400 V,on request: up to 1000 V
Tolerance L	±5%
L value (mH)	1.92
Insulation voltage, circuit	3 kV
Electrical characteristic	
Overvoltage factor (p %)	7 % (189 Hz)
Mechanical characteristics	
Size (mm) width x height x depth	235 x 165 x 125 (mm)
Envelope	Conductor type: Aluminium strip / copper cable
Weight (kg)	12
Environmental characteristics	
Thermal Class	class F (+155 °C) On request: class H (+180 °C)
Protection class	IP 00
Installation, location, position.	Inside
Ambient temperature	-10 +45 °C
Standards	
Standards	UNE-EN 60289, IEC 60076
Protection	

#### RZ-RBZ

Reactors III for detuned filters

CODE	TYPE	L(mH)	For capacitor	In (A) Frequency (Hz)	kvar (400 V)	Losses	Un (V)	Р%	
------	------	-------	---------------	-----------------------	-----------------	--------	--------	----	--

400 Vac, 50 Hz, f resonance = 189 Hz / p=7%







# **RBZ-20-400**

Reactors

Code: P73125.

CODE	TYPE	L(mH)	For capacitor	In (A)	Frequency (Hz)	kvar (400 V)	Losses	Un (V)	Р%
P73110.	RZ-5-400	7,66	CLZ-FP-46/6,25	7,2	50	5	26	400	7%
P73112.	RZ-6,25-400	6,1	CLZ-FP-52/10	9	50	6,25	33	400	7%
P73115.	RZ-10-400	3,83	CLZ-FP-46/12,5	15	50	10	52	400	7%
P73117.	RZ-12,5-400	3,05	CLZ-FP-46/15	18	50	12,5	57	400	7%
P73120.	RZ-15-400	2,55	CLZ-FP-46/19	22	50	15	59	400	7%
P73125.	RBZ-20-400	1,91	CLZ-FP-46/25	29	50	20	79	400	7%
P73130.	RBZ-25-400	1,53	CLZ-FP-46/30	36	50	25	93	400	7%
P73135.	RBZ-30-400	1,27	2 x CLZ-FP-46/19	43	50	30	124	400	7%
P73140.	RBZ-40-400	0,95	2 x CLZ-FP-46/25	58	50	40	149	400	7%
P73145.	RBZ-50-400	0,76	2 x CLZ-FP-46/30	72	50	50	189	400	7%
P73150.	RBZ-60-400	0,63	3 x CLZ-FP-46/25	87	50	60	210	400	7%
P73155.	RBZ-80-400	0,48	3 x CLZ-FP-46/33,3	115	50	80	241	400	7%









## **RBZ-20-400**

Reactors

Code: P73125.

### **Dimensions**





Tipo	A mm	B mm	C mm	D* mm	E* mm	F mm	G mm	kg
RBZ-20-400	235	125	165	150	95	7	145	14
RBZ-25-400	235	125	165	150	95	7	145	14
RBZ-30-400	255	125	200	160	95	9	150	19
RBZ-40-400	255	125	200	160	95	9	150	20
RBZ-50-400	255	145	220	160	115	9	175	25
RBZ-60-400	255	145	240	180	115	9	175	28
RBZ-80-400	305	155	255	180	115	11	190	31

Tipo	A mm	B mm	C mm	D* mm	E* mm	F mm	G mm	kg	
RBEZ-40-400	300	145	235	160	113	9	180	30	
RBEZ-50-400	300	145	235	160	113	9	180	30	
RBEZ-60-400	300	145	235	160	113	9	180	30	
RBEZ-80-400	345	155	255	180	121	11	195	40	
* Distance between fixations									



