



CEM-D212 -MID, Direct three-phase energy meter with MID certificate

Code: Q22622.

> Protocol: MBUS> Módules: 4> Certification: MID> Digital inputs: 2> System: Three-phase

> Measure: Direct

> Measurement Range (V): 3x127(230)...3x230(400)V

> Measurement Range (A): (5) 100A

### Description

Three-phase electrical energy meter with direct measurement up to 100 A (depending on model), featuring sealable terminals and optional communication via Modbus RS-485 and M-BUS protocols (depending on model).

Main features include:

- o MID certification, modules B+D (depending on model).
- o Class 1 for active energy (Class B as per MID), Class 2 for reactive energy.
- Compliant with EN 50470 (European MID standard) or IEC 62052-11 (international standard), depending on the model.
- o Compact size (4 DIN rail modules).
- o Resettable partial energy counter.
- o 1 programmable pulse output (depending on model).
- o 1 digital input for tariff control and pulse counting (depending on model).
- o Time-of-use tariff calendar.
- $\circ~$  Modbus RS-485 and M-BUS communications (depending on model).
- O Display of basic electrical parameters (V, A, kW, kWh, PF, etc.).

### **Application**

- Meter for energy sub-metering.
- o Applications where certified MID meters are required for energy verification and billing.
- o Meter used to verify the energy invoiced by the electricity distributor.
- o Energy consumption reporting and connectivity with SCADA systems.
- o Energy and cost control in industrial processes.







Three-phase electricity meter with direct measurement up to

Code: Q22622.

### Specifications

Installation category	CAT III 300 V					
Consumption	< 0.5 W, < 2 VA					
Frequency	50 60 Hz					
Nominal voltage	3 x 127/220 3 x 230/400 V ~ ± 20 %					
Mechanical characteristics						
Size (mm) width x height x depth	71.5 x 90 x 74 (mm)					
Envelope	PC+ABS					
Fastening	DIN rail (IEC 60715)					
Weight (kg)	0,38					
invironmental characteristics						
Protection class	IP 51 (instaled) IP 40 (terminal area)					
Relative humidity (without condensation)	5 95 %					
Storage temperature	-40 +85 °C					
Working temperature	-40 +70 °C					
Current measurement circuit						
Consumption	< 1 VA					
D ( 1/1 ()	5 A					
Reference current (Iref)	37.					
Minimum current measurement	0.250 A					
Minimum current measurement	0.250 A					
Minimum current measurement  Transition current	0.250 A					
Minimum current measurement  Transition current  foltage measurement circuit	0.250 A 0.500 A					
Minimum current measurement  Transition current  Oltage measurement circuit  Nominal voltage	0.250 A 0.500 A					
Minimum current measurement  Transition current  Yoltage measurement circuit  Nominal voltage  User interface	0.250 A 0.500 A 3 x 127/220 3 x 230/400 V ~ ± 20 %					
Minimum current measurement  Transition current  /oltage measurement circuit  Nominal voltage  User interface	0.250 A 0.500 A  3 x 127/220 3 x 230/400 V ~ ± 20 %  2 LED: kWh: 4000 imp/kWh, kvarh: 4000 imp/kvarh					
Minimum current measurement  Transition current  Voltage measurement circuit  Nominal voltage  User interface  LED  Keyboard	0.250 A 0.500 A  3 x 127/220 3 x 230/400 V ~ ± 20 %  2 LED: kWh: 4000 imp/kWh, kvarh: 4000 imp/kvarh 2 Keys					
Minimum current measurement  Transition current  foltage measurement circuit  Nominal voltage  User interface  LED  Keyboard  Display type	0.250 A  0.500 A  3 x 127/220 3 x 230/400 V ~ ± 20 %  2 LED: kWh: 4000 imp/kWh, kvarh: 4000 imp/kvarh 2 Keys LCD					
Minimum current measurement  Transition current  /oltage measurement circuit  Nominal voltage  Jeer interface  LED  Keyboard  Display type  Maximum value	0.250 A  0.500 A  3 x 127/220 3 x 230/400 V ~ ± 20 %  2 LED: kWh: 4000 imp/kWh, kvarh: 4000 imp/kvarh 2 Keys LCD					







Three-phase electricity meter with direct measurement up to 100A

Code: Q22622.

Standards

IEC-62053-21; IEC 62053-23; IEC 62053-52; IEC 62052-11; UNE-EN 50470-3; MID (EU Directive 2014/32/EU on Measuring Instruments Annex II, Module B  $\,$ 

### Digital transistor outputs

Туре	Optocoupler
Measurement accuracy	
Reactive energy measurement (kvarh)	Class 2 (IEC 62053-23)
Active energy measurement (kWh)	Class B (UNE-EN-50470)
Serial communication	
Protocol	MBUS

#### CEM-D200

Three-phase electricity meter with direct measurement up to 100A

CODE	TYPE	Measurement Range (V)	Measurement Range (A)	Transistor output	Certification	Módules	Digital inputs	Communications	Protocol
Direct the	ree-phase								
Q22601.	CEM-D210	3x127(230)3x230(400)V	(5) 100A	1	IEC	4			
Q22602.	CEM-D210 -MID	3x127(230)3x230(400)V	(5) 100A	1	MID	4			
Q22611.	CEM-D211	3x127(230)3x230(400)V	(5) 100A		IEC	4	2	RS-485	Modbus/RTU
Q22612.	CEM-D211 -MID	3x127(230)3x230(400)V	(5) 100A		MID	4	2	RS-485	Modbus/RTU
Q22621.	CEM-D212	3x127(230)3x230(400)V	(5) 100A		IEC	4	2		MBUS
Q22622.	CEM-D212 -MID	3x127(230)3x230(400)V	(5) 100A		MID	4	2		MBUS









Three-phase electricity meter with direct measurement up to 100A

Code: Q22622.

Dimensions Connections







3Ph-4W



3Ph-3W