

TRMC-X3 400/5 Ext

TRMC-X3 400/5 Ext, Current transformers

Code: Q301T4010E000

> Usefull diam.(mm): 38
> Cable (m): 6
> Class 0,5S Power (VA): 2,5
> Measurement Range (A): 300/5

Specifications

AC power supply

Frequency	50 / 60 Hz

Electrical characteristics

Safety factor (SF)	5
Power	2,5 ... 5 VA
Insulation voltage, circuit	3 kV

Mechanical characteristics

Size (mm) width x height x depth	245 x 80 x 98.5 (mm)
Envelope	Self-extinguishing V0 plastic, filled with synthetic resin
Weight (kg)	2,2

Environmental characteristics

Thermal Class	class B (+130 °C)
Relative humidity (without condensation)	5 ... 95 %
Installation, location, position.	Inside
Storage temperature	-15 ... +50 °C
Working temperature	-5 ... +40 °C

Specific technical characteristics of current sensors

Operating voltage	0,72 kV~ máx.

Standards

Certifications	UL 94
Electrical safety, Maximum height (m)	1000
Standards	IEC 61869-2, IEC 60038, IEC 60071-1, IEC 60071-2, IEC 60721-3-3, IEC 60085, EN 60076-5, UNE 21-305-90, UNE-EN 60695-2-10, UNE-EN 60695-2-11, UL 94

Current measurement circuit

Primary current measurement	400 A
Dynamic current (Idyn)	2,5 Ith
Thermal short-circuit current (Ith)	60 In
Transformation ratio	... / 5 A



TRMC-X3 400/5 Ext

Code: Q301T4010E000

TRMCx3
Three-phase current transformers for energy meters

CODE	TYPE	Measurement Range (A)	Class 0,5S Power (VA)	Inner diameter (mm)	Cable (m)
Outdoor					
Q301T1010E000	TRMC-X3 100/5 Ext	100/5	2,5	38	6
Q301T2010E000	TRMC-X3 200/5 Ext	200/5	2,5	38	6
Q301T3010E000	TRMC-X3 300/5-Ext	300/5	2,5	38	6
Q301T4010E000	TRMC-X3 400/5 Ext	400/5	2,5	38	6


Creation date: 21/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.




TRMC-X3 400/5 Ext

Code: Q301T4010E000

Dimensions



Connections



Creation date: 21/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.