



Compact DC-S BASIC

Compact DC-S BASIC, PRIME PLC Concentrator

Code: Q46240. CONSULTAR DISPONIBILIDAD

- > 2nd transformer connection: No
- > Homologation: -
- > Communications: PRIME | 3G
- > Digital inputs: -
- > LV supervisor: No

Description

The **COMPACT DC** concentrator is the device used to manage and read three-phase and single-phase power meters connected to the same low-voltage network using PRIME communications.

Typically located in the transformer substation, the **COMPACT DC** concentrator provides telemanagement features for the meters, whether reading the information they provide, or executing the actions that can be applied to this type of device, such as modifying tariffs, actuating the circuit breaker, etc.

 ${\sf COMPACT}\ {\sf DC}$ has an indirect three-phase meter with low-voltage monitoring functions, depending on the model.

The device features PRIME PLC communications, an Ethernet port and digital inputs.

Circutor

Page 2 of 3



Compact DC-S BASIC

PLC PRIME Concentrator

Code: Q46240.

Specifications

Installation category	CAT III 300V
Consumption	10 26 VA
Frequency	50 / 60 Hz
Nominal voltage	110 230 V~ ±20 %
Mechanical characteristics	
Size (mm) width x height x depth	165 x 120 x 130 (mm)
Envelope	Self-extinguishing V0 plastic
Fastening	DIN rail
Weight (kg)	0,95
Environmental characteristics	
Protection class	IP40
Relative humidity (without condensation)	5 95 %
Working temperature	-25 +70 °C
/oltage measurement circuit	
Frequency measuring range	45 65 Hz
Voltage measuring range	127/220 230/400 V~ ±20 %
Communication Network	
Technology / Type	PRIME
Standards	
Electrical safety, Maximum height (m)	2000
Standards	UNE-EN 61000-4-2, UNE-EN 61000-4-3, UNE-EN 61000-4-4, UNE-EI 61000-4-5, UNE-EN 62052-11, IEC 61010
User interface	
User interface	13 indication LEDs
	13 indication LEDs
LED	13 indication LEDs SMA female connector
LED	
LED Radio communication -Antenna	



Compact DC-S BASIC

PLC PRIME Concentrator

Code: Q46240.

Dimensions

×

