

PS HDR-30-12

PS HDR-30-12, 12 Vdc, 2A power supply,

Code: Q4994L.

Specifications

AC power supply

Frequency	47 ~ 63 Hz
Nominal voltage	85 ... 264 Vca (± 5%)

DC power supply

Nominal voltage	120 ... 370 Vdc (± 5%)

Mechanical characteristics

Size (mm) width x height x depth	35 x 90 x 54.5 (mm)
Weight (kg)	0,1

Environmental characteristics

Relative humidity (without condensation)	20 ... 90 %
Working temperature	-40 ... +85 °C

Standards

Certifications	UL62368-1, UL508, TÜV, EAC (TP TC 004), BSMI, BIS
Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT II
Standards	EN61558, EN50178, EN60664-1, EN62477-1, UL62368-1, UL508, BS EN/EN61558-2-16, BS EN/EN61558-1, IEC62368-1, EAC TP TC 004, BSMI CNS15598-1, BIS IS13252 (Part 1):2010 / IEC 60950-1:2006, EN55032 (CISPR32) Class B, EN61000-3-2 Class A, EN61000-3-3, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-8, EN61000-4-11, IEC60068-2-6

Electrical safety

Insulation	Class II

Power supply


Maximum output voltage / current	12 Vcc / 2 A

Power supply output

Power	24 W
Voltage	12 Vcc

Fuente Alimentación
Power Supply

Creation date: 24/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



PS HDR-30-12

Router industrial

Code: Q4994L.

CODE	TYPE	Description
Q4994L.	PS HDR-30-12	12 Vdc power supply

Creation date: 24/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.