



410-QD1A-B3B12, Three-phase energy meters direct connection

Code: QB4M1D20 DESCATALOGADO

> Type Consumer: 5

> Discon. relay: Yes

> Communications: - | PRIME

> N° relays: 1

> Class (Active/Reactive): B (1) / 2

> System: Three-phase

> Measure: Direct

> Measurement Range (V): 3x230/400 > Measurement Range (A): 10 (100)

> Quadrants: 4

> Frequency (Hz): 50

#### Description

The **CIRWATT B 410RCP** is a digital multifunction three-phase class-B/Class-1 meter for active energy and Class-2 for reactive energy. This meter complies with the international IEC 62053-21 and IEC 62053-23 standards, and with the European regulations on energy meters, EN 50470-1 and EN 50470-3 (MID), which allows them to be installed in any European Union country.

It features PLC (Prime Line Carrier) PRIME communications via the electrical grid, as well as an optical port. Both communications use the DLMS protocol. It also has a logger for up to 3 months of time records for the 6 types of energy. It also allows the data to be read in the absence of voltage. It includes a circuit breaker, which allows the user to control the electricity demand, which can be managed remotely using PLC communications.

#### **Application**

The main application of the **CIRWATT B410RCP** meter is to measure active and reactive energy for invoicing in those cases where a high-performance meter is required at an optimized cost. PLC communication allows all the data recorded by the meter to be downloaded remotely via the Compact DC concentrator with PLC PRIME communication.

The circuit breaker integrated into the meter allows the supply to be managed remotely by interrupting or restoring the electricity to any user. It is also used to program the power contracted. If the programmed power exceeds its threshold, the circuit breaker will trip, cutting the supply or restoring it safely once the consumption is below the programmed threshold, thus ensuring the end user's safety at all times.







Three-phase energy meters direct connection

Code: QB4M1D20

### **Specifications**

0 % 115 % Un 2 W; < 10 VA 0 / 60 Hz x 230 (400) V  20 years (e) 30 °C chium  2 x 230 x 67 (mm) N 43859 0 6 % max. 0 +85 °C 0 +70 °C
20 years (a 30 °C chium 2 x 230 x 67 (mm) N 43859 C C c c c c c c c c c c c c c c c c c
x 230 (400) V  20 years @ 30 °C  chium  2 x 230 x 67 (mm)  N 43859  9  6 % max.  0 +85 °C  0 +70 °C
20 years @ 30 °C chium  2 x 230 x 67 (mm)  N 43859  6 % max.  0 +85 °C  0 +70 °C
2 x 230 x 67 (mm) N 43859 6 % max. 0 +85 °C 0 +70 °C
2 x 230 x 67 (mm) N 43859 6 % max. 0 +85 °C 0 +70 °C
2 x 230 x 67 (mm) N 43859 9 5 % max. 0 +85 °C
N 43859 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9
N 43859 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9
9 5 % max. 0 +85 °C 0 +70 °C
5 % max. 0 +85 °C 0 +70 °C
0 +85 °C 0 +70 °C
0 +85 °C 0 +70 °C
0 +70 °C
ymmetrical
2 W; 10 VA
) / 60 Hz
230/400 V
0,1 VA
A
0 A
0,5 x ltr
C 62056-21
MS
rial;bi-directional
rial;bi-directional
Εl







Three-phase energy meters direct connection

Code: QB4M1D20

Display type	LCD
Memory	
Memory capacity	Data: non-volatile memory, Setup and events: serial-flash
Write time	90 days
Туре	Serial flash
PLC	
Hardware	CENELEC
Protocol	DLMS / PRIME
Modulation system	OFDM
Measurement accuracy	
Reactive energy measurement (kvarh)	IEC 62053-23 (Class 2)
Active energy measurement (kWh)	EN 50470 (Class B) IEC 62053-21 (Class 1)
Features / performance	
Billing closures	12 locks per contract. Programable date and hour
Load curve	1 load curves, programmable integration time (1 60 min)
Tariff programming	12 days 24 types of data 6 types of tariffs 30 public holidays
Clock	
Source	Temperature compensated oscillator
Accuracy (EN 61038)	< 0,5 s/day (23 °C)
Туре	Gregorian calendar







Three-phase energy meters direct connection

Code: QB4M1D20

### Connections



