



410-QT5A-90B10-TRMC210-200-3.0.2, Three-phase energy meter indirect connection

Code: QB870T02 DESCATALOGADO

> Type Consumer: 3

> Communications: RS-232 | RS-485 > Class (Active/Reactive): B (1) / 2

> System: Three-phase > Measure: Indirect

> Measurement Range (V): 3x230/400 > Measurement Range (A): .../5

> Quadrants: 4 > Frequency (Hz): 50

### Description

CIRWATT-B410T is an indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21 and Class 2 reactive energy as per IEC-62053-23, with multiple communications options and expansion modules that allow it to be adapted to any type of industrial and tertiary sector installation.

#### **Application**

CIRWATT B-410T is perfect for low- and medium-voltage supplies using external current transformers. Offering solutions for a wide variety of installations such as: shopping centres, industries and highconsumption residential areas (Consumer type 3). Available in 2 quadrants for energy consumption or 4 quadrants for photovoltaic plants (energy generation and consumption).







Indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21

Code: QB870T02

### **Specifications**

AC power supply	
Tolerance	80 % 115 % Un
Consumption	< 2 W; < 10 VA
Frequency	50 / 60 Hz
Nominal voltage	3 x 230 (400) V
Battery specification	
Performance-guarantee	> 20 years @ 30 °C
Туре	Lithium
Mechanical characteristics	
Size (mm) width x height x depth	172 x 255 x 67 (mm)
Envelope	DIN 43859
Weight (kg)	5,6
Environmental characteristics	
Relative humidity (without condensation)	95 % max.
Storage temperature	-40 +85 °C
Working temperature	-40 +70 °C
Voltage measurement circuit	
Connection	Asymmetrical
Consumption	< 2 W; 10 VA
Nominal frequency	50 / 60 Hz
Nominal voltage	3x230/400 V
Current measurement circuit	
Consumption	< 0,1 V·A
Reference current (Iref)	/ 5 A
Maximum current	10 A
Minimum current measurement	< 0,5 x ltr
Optical communication interface	
Hardware	IEC 62056-21
Protocol	REE, based on IEC 870-5-136
Туре	Serial;bi-directional







Indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21

Code: QB870T02

#### User interface

Resolution of the display	up to 8 digits (8 mm)		
Display type	LCD		

#### Memory

Memory capacity	Data: non-volatile memory, Setup and events: serial-flash
Write time	4000
Туре	Serial flash

#### PLC

Hardware	CENELEC A or CENELEC B
Protocol	CirPLC & PEP (PLC Encapsulated Protocol)
Modulation system	DSCK with repeater system

#### Measurement accuracy

Reactive energy measurement (kvarh)	IEC 62053-23 (Class 2)
Active energy measurement (kWh)	EN 50470 (Class B) IEC 62053-21 (Class 1)

#### Features / performance

Billing closures	12 locks per contract. Programable date and hour			
Load curve 2 load curves, programmable integration time (1 253				
Optional	Communications: RS-232 / PLC, RS-485 / PLC, RS-232 / RS-232 , RS-485 / RS-485, RS-232 / RS-485, RS-232 / Ethernet, R-485 / Ethernet. Expansion boards: No inputs / outputs, 4 relay outputs (Rate Indicator), 2 relay inputs / 4 pulse outputs, 4 pulse inputs, Differential current measurement, 2 relay outputs / 2 pulse outputs, / 2 pulse inputs			
Tariff programming	12 days 10 types of data 9 types of tariffs 30 public holidays 12 special days			

### Clock

Source	Temperature compensated oscillator
Accuracy (EN 61038)	< 0,5 s/day (23 °C)
Туре	Gregorian calendar

#### CIRWATT B 410T

Indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21

CODE	ТҮРЕ	Measurement Range (V)	Measurement Range (A)	Communications	Class (Active/Reactive)	System	Measure		
CIRWATT B 410T									
QB860	410-QT5A-70B10	3x230/400	/5	RS-232   RS-232	B (1) / 2	Three-phase	Indirect		

**CIRWATT B 505** 







Indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21

Code: QB870T02

CODE	ТҮРЕ	Measurement Range (V)	Measurement Range (A)	Communications	Class (Active/Reactive)	System	Measure		
QBN40	410-VT7B-A0B10	3x57/100 3x230/400	/ 1	RS-232   Ethernet	C (0,5S)/1	Three-phase	Indirect		
CIRWATT B	CIRWATT B 410T								
QB8A0	410-QT5A-80B10	3x230/400	/5	RS-485   RS-485	B (1) / 2	Three-phase	Indirect		
QB870	410-QT5A-90B10	3x230/400	/5	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QB870T21	410-QT5A-90B10-TRMC210-100-3.0.TD	3x230/400	/5	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QB870T22	410-QT5A-90B10-TRMC210-200-3.0.TD	3x230/400	/5	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QB870T23	410-QT5A-90B10-TRMC210-500-3.0.TD	3x230/400	/5	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QB880	410-QT5A-A0B10	3x230/400	/5	RS-232   Ethernet	B (1) / 2	Three-phase	Indirect		
QB890	410-QT5A-C0B10	3x230/400	/5	RS-485   Ethernet	B (1) / 2	Three-phase	Indirect		
QBJ10	410-VT5A-90B10	3x57/100 3x230/400	/5	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QBG60	410-NT5A-70B10	3x127/220	/5	RS-232   RS-232	B (1) / 2	Three-phase	Indirect		
QBJ20	410-VT5A-A0B10	3x57/100 3x230/400	/5	RS-232   Ethernet	B (1) / 2	Three-phase	Indirect		
QBG70	410-NT5A-90B10	3x127/220	/5	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QB8D0	410-QT5B-90B10	3x230/400	/5	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QBGA0	410-NT5A-80B10	3x127/220	/5	RS-485   RS-485	B (1) / 2	Three-phase	Indirect		
QBG80	410-NT5A-A0B10	3x127/220	/5	RS-232   Ethernet	B (1) / 2	Three-phase	Indirect		
QB8E0	410-QT5B-A0B10	3x230/400	/5	RS-232   Ethernet	B (1) / 2	Three-phase	Indirect		
QBG90	410-NT5A-C0B10	3x127/220	/5	RS-485   Ethernet	B (1) / 2	Three-phase	Indirect		
QBJ60	410-VT5B-90B10	3x57/100 3x230/400	/5	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QBH20	410-MT5A-70B10	3x63,5/110	/5	RS-232   RS-232	B (1) / 2	Three-phase	Indirect		
QBJ70	410-VT5B-A0B10	3x57/100 3x230/400	/5	RS-232   Ethernet	B (1) / 2	Three-phase	Indirect		
QBH30	410-MT5A-90B10	3x63,5/110	/5	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QBNOB	410-QT7A-90B10	3x230/400	/ 1	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QBH61	410-MT5A-80B10	3x63,5/110	/5	RS-485   RS-485	B (1) / 2	Three-phase	Indirect		
QBH40	410-MT5A-A0B10	3x63,5/110	/5	RS-232   Ethernet	B (1) / 2	Three-phase	Indirect		
QBN1B	410-QT7A-A0B10	3x230/400	/ 1	RS-232   Ethernet	B (1) / 2	Three-phase	Indirect		
QBH50	410-MT5A-C0B10	3x63,5/110	/5	RS-485   Ethernet	B (1) / 2	Three-phase	Indirect		
QBNOJ	410-VT7A-90B10	3x57/100 3x230/400	/ 1	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QBN1J	410-VT7A-A0B10	3x57/100 3x230/400	/ 1	RS-232   Ethernet	B (1) / 2	Three-phase	Indirect		
QBN2B	410-QT7B-90B10	3x230/400	/ 1	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QBN3B	410-QT7B-A0B10	3x230/400	/ 1	RS-232   Ethernet	B (1) / 2	Three-phase	Indirect		
QBN2J	410-VT7B-90B10	3x57/100 3x230/400	/ 1	RS-232   RS-485	B (1) / 2	Three-phase	Indirect		
QBN3J	410-VT7B-A0B10	3x57/100 3x230/400	/ 1	RS-232   Ethernet	B (1) / 2	Three-phase	Indirect		

Please contact us for other configurations (Inputs, outputs and other communications)







Indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21

Code: QB870T02

### **Dimensions**



