



410-QT5A-B0B10

410-QT5A-B0B10, Three-phase energy meter indirect connection

Code: QB810 CONSULTAR DISPONIBILIDAD

- > Type Consumer: 3
- > Discon. relay: No
- > Communications: RS-232 | PRIME
- > N° relays: 0
- > Class (Active/Reactive): B (1) / 2
- > System: Three-phase
- > Measure: Indirect
- > Measurement Range (V): 3x230 / 400
- > Measurement Range (A): .../5
- > Quadrants: 4
- > Frequency (Hz): 50

Specifications

Mechanical characteristics

Size (mm) width x height x depth	172 x 255 x 67 (mm)
Envelope	DIN 43859
Weight (kg)	0,95

Environmental characteristics

Relative humidity (without condensation)	95 % max.
Storage temperature	-40 ... +85 °C
Working temperature	-40 ... +70 °C

Current measurement circuit

Consumption	< 0,1 VA
Reference current (Iref)	5 A
Maximum current	10 A
Minimum current measurement	< 0,2 x Itr

Communication Network

Technology / Interface	PRIME
------------------------	-------

Optical communication interface

Hardware	IEC 62056-21
Protocol	DLMS
Type	Serial;bi-directional

User interface

Resolution of the display	up to 8 digits (8 mm)
Display type	LCD

PLC



410-QT5A-B0B10

Three-phase energy meter indirect connection

Code: QB810

Hardware

CENELEC

Protocol

DLMS / PRIME

Modulation system

OFDM

Measurement accuracy

Reactive energy measurement (kvarh) IEC 62053-23 (Class 2)

Active energy measurement (kWh) EN 50470 (Class B) IEC 62053-21 (Class 1)

Features / performance

Billing closures 12 locks per contract. Programmable date and hour

Load curve 1 load curves, programmable integration time (1 ... 60 min)

Tariff programming 12 days 24 types of data 6 types of tariffs 30 public holidays

Clock

Source Temperature compensated oscillator

Accuracy (EN 61038) < 0,5 s/day (23 °C)

Type Gregorian calendar

Serial communication

Technology / Type RS-232





410-QT5A-B0B10

Three-phase energy meter indirect connection

Code: QB810

Dimensions



Connections

