



410-NT5A-COB10

410-NT5A-COB10, Three-phase energy meter indirect connection

Code: QBG90

> Type Consumer: 3

> Communications: RS-485 | Ethernet > Class (Active/Reactive): B (1) / 2

> System: Three-phase > Measure: Indirect

> Measurement Range (V): 3x127/220 > Measurement Range (A): .../5

> Quadrants: 4 > Frequency (Hz): 50

Description

CIRWATT-B410T is an indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21 and Class 2 reactive energy as per IEC-62053-23, with multiple communications options and expansion modules that allow it to be adapted to any type of industrial and tertiary sector installation.

Application

CIRWATT B-410T is perfect for low- and medium-voltage supplies using external current transformers. Offering solutions for a wide variety of installations such as: shopping centres, industries and highconsumption residential areas (Consumer type 3). Available in 2 quadrants for energy consumption or 4 quadrants for photovoltaic plants (energy generation and consumption).







Indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21

Code: QBG90

Specifications

AC power supply		
Tolerance	80 % 115 % Un	
Consumption	< 2 W; < 10 VA	
Frequency	50 / 60 Hz	
Nominal voltage	3 x 127 (220) V	
Battery specification		
Performance-guarantee	> 20 years @ 30 °C	
Туре	Lithium	
Mechanical characteristics		
Size (mm) width x height x depth	172 x 255 x 67 (mm)	
Envelope	DIN 43859	
Environmental characteristics		
Relative humidity (without condensation)	95 % max.	
Storage temperature	-40 +85 °C	
Working temperature	-40 +70 °C	
Voltage measurement circuit		
Connection	Asymmetrical	
Consumption	< 2 W; 10 VA	
Nominal frequency	50 / 60 Hz	
Nominal voltage	3x127/220 V	
Current measurement circuit		
Consumption	< 0,1 V·A	
Reference current (Iref)	/ 5 A	
Maximum current	10 A	
Minimum current measurement	< 0,5 x ltr	
Communication Network		
Protocol	REE, basado en IEC 870-5-102	
Technology / Type	Ethernet	
Optical communication interface		
Hardware	IEC 62056-21	







Indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21

Code: QBG90

rotocol REE, based on IEC 870-5-127				
Туре	Serial;bi-directional			
Jser interface				
Resolution of the display	up to 8 digits (8 mm)			
Display type	LCD			
1emory				
Memory capacity	Data: non-volatile memory, Setup and events: serial-flash			
Write time	4000			
Туре	Serial flash			
Standards				
Standards	UNE-EN 50470-1 Electricity metering equipment (a.c.) Part 1: General requirements, tests and test conditions - Metering equipment -class indexes B-) UNE-EN 50470-3 Electricity metering equipment (a.c.) Part 3: Particular requirements - Static meters for active energy -class indexes B-) IEC 62052-11, IEC 62053-21, IEC 62053-22 (Standards for static active energy meters for alternating current of class 0.2s, 0.5s) UNE-EN 55022 (Conducted Emissions: Class B, Radiated Emissions: Class B) UNE-EN 61000-4-2, UNE-EN 61000-4-3, UNE-EN 61000-4-4, UNE-EN 61000-4-5, UNE-EN 61000-4-6, UNE-EN 61000-4-8, UNE-EN 61000-4-11			
PLC				
Hardware	CENELEC A or CENELEC B			
Protocol	CirPLC & PEP (PLC Encapsulated Protocol)			
Modulation system	DSCK with repeater system			
deasurement accuracy				
Reactive energy measurement (kvarh)	IEC 62053-23 (Class 2)			
Active energy measurement (kWh)	EN 50470 (Class B) IEC 62053-21 (Class 1)			
eatures / performance				
Billing closures	12 locks per contract. Programable date and hour			
Load curve	2 load curves, programmable integration time (1 253 min)			
Optional	Communications: RS-232 / PLC ,RS-485 / PLC ,RS-232 / RS-232 , RS-485 / RS-485 , RS-485 , RS-232 / RS-485 , RS-232 / Ethernet, R-485 / Ethernet. Expansion boards: No inputs / outputs, 4 relay outputs (Rate Indicator), 2 relay inputs / 4 pulse outputs, 4 pulse inputs , Differential current measurement, 2 relay outputs / 2 pulse outputs, / 2 pulse inputs			
Tariff assassamming	12 days 10 types of data 9 types of tariffs 30 public holidays 12 special days			
Tariff programming				
Clock				







Indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21

Code: QBG90

Accuracy (EN 61038)	< 0,5 s/day (23 °C)
Туре	Gregorian calendar
Serial communication	
Protocol	REE, basado en IEC 870-5-102
Technology / Type	RS-485

CIRWATT B 410T

Indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21

CODE	ТҮРЕ	Measurement Range (V)	Measurement Range (A)	Communications	Class (Active/Reactive)	System	Measure
CIRWATT B	410T						
QB860	410-QT5A-70B10	3x230/400	/5	RS-232 RS-232	B (1) / 2	Three-phase	Indirect
CIRWATT B	505						
QBN40	410-VT7B-A0B10	3x57/100 3x230/400	/ 1	RS-232 Ethernet	C (0,5S)/1	Three-phase	Indirect
CIRWATT B	410T						
QB8A0	410-QT5A-80B10	3x230/400	/5	RS-485 RS-485	B (1) / 2	Three-phase	Indirect
QB870	410-QT5A-90B10	3x230/400	/5	RS-232 RS-485	B (1) / 2	Three-phase	Indirect
QB870T21	410-QT5A-90B10-TRMC210-100-3.0.TD	3x230/400	/5	RS-232 RS-485	B (1) / 2	Three-phase	Indirect
QB870T22	410-QT5A-90B10-TRMC210-200-3.0.TD	3x230/400	/5	RS-232 RS-485	B (1) / 2	Three-phase	Indirect
QB870T23	410-QT5A-90B10-TRMC210-500-3.0.TD	3x230/400	/5	RS-232 RS-485	B (1) / 2	Three-phase	Indirect
QB880	410-QT5A-A0B10	3x230/400	/5	RS-232 Ethernet	B (1) / 2	Three-phase	Indirect
QB890	410-QT5A-C0B10	3x230/400	/5	RS-485 Ethernet	B (1) / 2	Three-phase	Indirect
QBJ10	410-VT5A-90B10	3x57/100 3x230/400	/5	RS-232 RS-485	B (1) / 2	Three-phase	Indirect
QBG60	410-NT5A-70B10	3x127/220	/5	RS-232 RS-232	B (1) / 2	Three-phase	Indirect
QBJ20	410-VT5A-A0B10	3x57/100 3x230/400	/5	RS-232 Ethernet	B (1) / 2	Three-phase	Indirect
QBG70	410-NT5A-90B10	3x127/220	/5	RS-232 RS-485	B (1) / 2	Three-phase	Indirect
QB8D0	410-QT5B-90B10	3x230/400	/5	RS-232 RS-485	B (1) / 2	Three-phase	Indirect
QBGA0	410-NT5A-80B10	3x127/220	/5	RS-485 RS-485	B (1) / 2	Three-phase	Indirect
QBG80	410-NT5A-A0B10	3x127/220	/5	RS-232 Ethernet	B (1) / 2	Three-phase	Indirect
QB8E0	410-QT5B-A0B10	3x230/400	/5	RS-232 Ethernet	B (1) / 2	Three-phase	Indirect
QBG90	410-NT5A-C0B10	3x127/220	/5	RS-485 Ethernet	B (1) / 2	Three-phase	Indirect
QBJ60	410-VT5B-90B10	3x57/100 3x230/400	/5	RS-232 RS-485	B (1) / 2	Three-phase	Indirect
QBH20	410-MT5A-70B10	3x63,5/110	/5	RS-232 RS-232	B (1) / 2	Three-phase	Indirect
QBJ70	410-VT5B-A0B10	3x57/100 3x230/400	/5	RS-232 Ethernet	B (1) / 2	Three-phase	Indirect
QBH30	410-MT5A-90B10	3x63,5/110	/5	RS-232 RS-485	B (1) / 2	Three-phase	Indirect
QBN0B	410-QT7A-90B10	3x230/400	/ 1	RS-232 RS-485	B (1) / 2	Three-phase	Indirect
QBH61	410-MT5A-80B10	3x63,5/110	/5	RS-485 RS-485	B (1) / 2	Three-phase	Indirect
QBH40	410-MT5A-A0B10	3x63,5/110	/5	RS-232 Ethernet	B (1) / 2	Three-phase	Indirect
QBN1B	410-QT7A-A0B10	3x230/400	/ 1	RS-232 Ethernet	B (1) / 2	Three-phase	Indirect
QBH50	410-MT5A-C0B10	3x63,5/110	/5	RS-485 Ethernet	B (1) / 2	Three-phase	Indirect
QBNOJ	410-VT7A-90B10	3x57/100 3x230/400	/ 1	RS-232 RS-485	B (1) / 2	Three-phase	Indirect







Indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21

Code: QBG90

CODE	TYPE	Measurement Range (V)	Measurement Range (A)	Communications	Class (Active/Reactive)	System	Measure
QBN1J	410-VT7A-A0B10	3x57/100 3x230/400	/ 1	RS-232 Ethernet	B (1) / 2	Three-phase	Indirect
QBN2B	410-QT7B-90B10	3x230/400	/ 1	RS-232 RS-485	B (1) / 2	Three-phase	Indirect
QBN3B	410-QT7B-A0B10	3x230/400	/ 1	RS-232 Ethernet	B (1) / 2	Three-phase	Indirect
QBN2J	410-VT7B-90B10	3x57/100 3x230/400	/ 1	RS-232 RS-485	B (1) / 2	Three-phase	Indirect
QBN3J	410-VT7B-A0B10	3x57/100 3x230/400	/ 1	RS-232 Ethernet	B (1) / 2	Three-phase	Indirect

 ${\it Please contact us for other configurations (Inputs, outputs and other communications)}$







Indirect multi-rate three-phase meter and logger, Class B in active energy as per the European MID Directive (EN 50470), or Class 1 as per IEC-62053-21

Code: QBG90

Dimensions Connections





