



405-VT7A-A0B10, Three-phase energy meter indirect connection

Code: QBN10

> Communications: RS-232 | Ethernet > Class (Active/Reactive): C (0,5S)/1

> System: Three-phase> Measure: Indirect

> Measurement Range (V): 3x57/100 ... 3x230/400

> Measurement Range (A): .../ 1

> Quadrants: 4 > Frequency (Hz): 50

#### Description

The CIRWATT-B505 is an indirect three-phase meter, recorder, and multi-tariff device, classified as Class C for active energy as per the European MID Directive (EN 50470) or Class 0.5s as per IEC-62053-22, and reactive energy Class 1 as per IEC-62053-23. It offers multiple communication options and expansion modules, allowing it to adapt to any type of industrial or tertiary sector installation.

#### **Application**

CIRWATT B-505 is ideal for medium-voltage supplies using external voltage and current transformers. Offering solutions for large industry with a power between 450 kW and 10 MW (Consumer type 2). Available in 2 quadrants for energy consumption or 4 quadrants for photovoltaic plants (energy generation and consumption).







Indirect three-phase meter, recorder, and multi-tariff device, classified as Class C for active energy as per the European MID Directive (EN 50470) or Class 0.5s as per IEC-62053-22

Code: QBN10

#### **Specifications**

AC power supply	
Tolerance	80 % 115 % Un
Consumption	< 2 W; < 10 VA
Frequency	50 / 60 Hz
Nominal voltage	3 x 57 (100) V 3 x 230 (400) V
Battery specification	
Performance-guarantee	> 20 years @ 30 °C
Туре	Lithium
Mechanical characteristics	
Size (mm) width x height x depth	172 x 255 x 67 (mm)
Envelope	DIN 43859
Environmental characteristics	
Relative humidity (without condensation)	95 % max.
Storage temperature	-40 +85 °C
Working temperature	-25 +70 °C
Voltage measurement circuit	
Connection	Asymmetrical
Consumption	< 2 W; 10 VA
Nominal frequency	50 / 60 Hz
Nominal voltage	3x57/100 3x230/400 V
Current measurement circuit	
Consumption	< 0,1 V·A
Reference current (Iref)	/ 5 A
Maximum current	10 A
Minimum current measurement	< 0,5 x ltr
Communication Network	
Protocol	REE, basado en IEC 870-5-102
Technology / Type	Ethernet
Optical communication interface	
Hardware	IEC 62056-21







Indirect three-phase meter, recorder, and multi-tariff device, classified as Class C for active energy as per the European MID Directive (EN 50470) or Class 0.5s as per IEC-62053-22

Code: QBN10

Protocol	REE, based on IEC 870-5-172		
Туре	Serial;bi-directional		
Jser interface			
Resolution of the display	up to 8 digits (8 mm)		
Display type	LCD		
Memory			
Memory capacity	Data: non-volatile memory, Setup and events: serial-flash		
Write time	4000		
Туре	Serial flash		
Standards			
Standards	UNE-EN 50470-1 Electricity metering equipment (a.c.) Part 1: General requirements, tests and test conditions - Metering equipment -class indexes B-) UNE-EN 50470-3 Electricity metering equipment (a.c.) Part 3: Particular requirements - Static meters for active energy -class indexes B-) IEC 62052-11, IEC 62053-21, IEC 62053-22 (Standards for static active energy meters for alternating current of class 0.2s, 0.5s) UNE-EN 55022 (Conducted Emissions: Class B, Radiated Emissions: Class B) UNE-EN 61000-4-2, UNE-EN 61000-4-3, UNE-EN 61000-4-4, UNE-EN 61000-4-5, UNE-EN 61000-4-6, UNE-EN 61000-4-8, UNE-EN 61000-4-11		
PLC			
Hardware	CENELEC A or CENELEC B		
Protocol	CirPLC & PEP (PLC Encapsulated Protocol)		
Modulation system	DSCK with repeater system		
Measurement accuracy			
Reactive energy measurement (kvarh)	IEC 62053-23 (Class 1 / 2)		
Active energy measurement (kWh)	IEC 62053-22 (Class 0,5S) EN 50470 (Class C)		
Features / performance			
Billing closures	12 locks per contract. Programable date and hour		
Load curve	2 load curves, programmable integration time (1 253 min)		
Optional	Communications: RS-232 / PLC ,RS-485 / PLC, RS-232 / RS-232 , RS-485 / RS-485, RS-232 / RS-485, RS-232 / Ethernet, R-485 / Ethernet. Expansion boards: No inputs / outputs, 4 relay outputs (Rate Indicator), 2 relay inputs / 4 pulse outputs, 4 pulse inputs, Differential current measurement, 2 relay outputs / 2 pulse outputs, / 2 pulse inputs		
Tariff programming	12 days 10 types of data 9 types of tariffs 30 public holidays 12 special days		
Clock			
Source	Temperature compensated oscillator		







Indirect three-phase meter, recorder, and multi-tariff device, classified as Class C for active energy as per the European MID Directive (EN 50470) or Class 0.5s as per IEC-62053-22

Code: QBN10

Accuracy (EN 61038)	< 0,5 s/day (23 °C)
Туре	Gregorian calendar
Serial communication	
Protocol	REE, basado en IEC 870-5-102
Technology / Type	RS-232

#### **CIRWATT B 505**

Indirect three-phase meter, recorder, and multi-tariff device, classified as Class C for active energy as per the European MID Directive (EN 50470) or Class 0.5s as per IEC-62053-22

CODE	TYPE	Measurement Range (V)	Measurement Range (A)	Communications	Class (Active/Reactive)	System	Measure
CIRWA	TT B 505						
QBP1I	405-MT5A-70B10	3x63,5/110	/5	RS-232   RS-232	C (0,5S)/1	Three-phase	Indirect
QBK10	405-VT5A-90B10	3x57/100 3x230/400	/5	RS-232   RS-485	C (0,5S)/1	Three-phase	Indirect
QBP1J	405-MT5A-80B10	3x63,5/110	/5	RS-485   RS-485	C (0,5S)/1	Three-phase	Indirect
QBP1E	405-MT5A-90B10	3x63,5/110	/5	RS-232   RS-485	C (0,5S)/1	Three-phase	Indirect
QBP1F	405-MT5A-A0B10	3x63,5/110	/5	RS-232   Ethernet	C (0,5S)/1	Three-phase	Indirect
QBP1K	405-MT5A-C0B10	3x63,5/110	/5	RS-485   Ethernet	C (0,5S)/1	Three-phase	Indirect
QBN00	405-VT7A-90B10	3x57/100 3x230/400	/ 1	RS-232   RS-485	C (0,5S)/1	Three-phase	Indirect
QBN10	405-VT7A-A0B10	3x57/100 3x230/400	/ 1	RS-232   Ethernet	C (0,5S)/1	Three-phase	Indirect
QBN30	405-VT7B-90B10	3x57/100 3x230/400	/ 1	RS-232   RS-485	C (0,5S)/1	Three-phase	Indirect

Please contact us for other configurations (Inputs, outputs and other communications)







Indirect three-phase meter, recorder, and multi-tariff device, classified as Class C for active energy as per the European MID Directive (EN 50470) or Class 0.5s as per IEC-62053-22

Code: QBN10

#### Dimensions Connections





