

CIRWATT Repeater



CIRWATT Repeater, Three-phase repeater to amplify the PLC system of the PRIME system (3 x 127/200 ... 3 x 230/ 400 V),
Code: QM4011.

Specifications

AC power supply		
Frequency		50 ... 60 Hz.
Nominal voltage		230 V ~ (F-N/Ph-N) - 400 V ~ (F-F/Ph-Ph)
Mechanical characteristics		
Size (mm) width x height x depth		200 x 120 x 55.15 (mm)
Envelope		ABS
Weight (kg)		0,465
Environmental characteristics		
Protection class		IP40
Relative humidity (without condensation)		5 ... 95%
Storage temperature		-30 ... +80°C
Working temperature		-25 ... +70°C
Standards		
Electrical safety, Maximum height (m)		2000
Standards		UNE-EN 61000-6-2, UNE-EN 61000-6-4, UNE-EN 61010-1
User interface		
LED		3 Indications LED
PLC		
Modulation system		OFDM

CIRWATT-repeater
Repeater for amplification of the PLC signal for the PRIME system

CODE	TYPE	Description
QM4011.	CIRWATT Repeater	Three-phase repeater to amplify the PLC system of the PRIME system (3 x 127/200 ... 3 x 230/ 400 V)



CIRWATT Repeater

Code: QM4011.

Dimensions

