

## CIRWATT Repeater



CIRWATT Repeater, Three-phase repeater to amplify the PLC system of the PRIME system (3 x 127/200 ... 3 x 230/ 400 V),

Code: QM4011.

### Specifications

#### AC power supply

|                 |  |
|-----------------|--|
| Frequency       | 50 ... 60 Hz.                            |
| Nominal voltage | 230 V ~ (F-N/Ph-N) - 400 V ~ (F-F/Ph-Ph) |

#### Mechanical characteristics

|                                  |                        |
|----------------------------------|------------------------|
| Size (mm) width x height x depth | 200 x 120 x 55.15 (mm) |
| Envelope                         | ABS                    |
| Weight (kg)                      | 0,465                  |

#### Environmental characteristics

|  |               |
|--|---------------|
| Protection class                         | IP40          |
| Relative humidity (without condensation) | 5 ... 95%     |
| Storage temperature                      | -30 ... +80°C |
| Working temperature                      | -25 ... +70°C |

#### Standards

|                                       |  |
|---------------------------------------|--|
| Electrical safety, Maximum height (m) | 2000   |
| Standards                             | UNE-EN 61000-6-2, UNE-EN 61000-6-4, UNE-EN 61010-1 |

#### User interface

|     |                   |
|-----|-------------------|
| LED | 3 Indications LED |
|-----|-------------------|

#### PLC

|                   |      |
|-------------------|------|
| Modulation system | OFDM |
|-------------------|------|

#### CIRWATT-repeater

Repeater for amplification of the PLC signal for the PRIME system

| CODE    | TYPE             | Description   |
|---------|------------------|---|
| QM4011. | CIRWATT Repeater | Three-phase repeater to amplify the PLC system of the PRIME system (3 x 127/200 ... 3 x 230/ 400 V) |



## CIRWATT Repeater

---

Code: QM4011.

## Dimensions

---

