



Computer C6 Wi-Fi, Power factor regulator

Code: R14831.

- > Alarm relay: Yes
- > Measurement Range (V): 400
- > Power supply (Vac): 400 Vac
- > Nr steps: 6
- > Input current: ... / 5A > Switching unit: Contactor

Description

The Computer C Wi-Fi series of regulators is designed for simple and effective regulation. Its high-contrast display can show up to 27 electrical parameters.

Its features are key to having a robust and reliable system, as well as to obtaining the necessary warnings and alarms for its proper monitoring and control:

- O Up to 12 fully configurable alarms.
- o Plug & Play.
- o For easier preventive maintenance

Application

The Computer C Wi-Fi is the ideal regulator to compensate balanced installations, where ease of programming, robustness, precision, and maximum compensation control are required. Its simple and intuitive programming system facilitates user installation and maintenance.







Power factor controller with communications

Fast power factor regulator

Code: R14831.

Specifications

| AC power supply | |
|--|---|
| Installation category | CAT III 300 V |
| Consumption | 13 VA |
| Frequency | 50 60 Hz |
| Nominal voltage | 400 V ~ (±10 %) |
| Mechanical characteristics | |
| Size (mm) width x height x depth | 144 x 144 x 54.85 (mm) |
| Envelope | Plastic VO self-extinguishing |
| Fastening | Panel |
| Weight (kg) | 0,43 |
| Environmental characteristics | |
| Protection class | IP 30 / Front Panel: IP 40 IK 08 |
| Relative humidity (without condensation) | 5 95 % |
| Storage temperature | -20 +70 °C |
| Working temperature | -20 +60 °C |
| Current measurement circuit | |
| Nominal current (In) | / 5 A |
| Phase current measuring range | 0.05 5A |
| Permanent overload | + 20% |
| Connection | Connect preferably to phase L1 |
| Standards | |
| Electrical safety, Maximum height (m) | 2000 |
| Electrical safety, Contamination level/class | Pollution resistance 2 |
| Standards | IEC 61010, IEC 61000-2-30, IEC 61000-6-4, IEC 61000-6-2 |
| Electrical safety | |
| Insulation | Double-insulated electric shock protection class II (IEC 61010-1) |
| User interface | |
| Resolution of the display | 3 digits |
| Keyboard | 3 keys |
| Digital relay outputs | |
| Quantity | 6 + 1 (Alarm) |
| Maximum current | 1 A~ |
| | |







Fast power factor regulator

Code: R14831.

| Maximum open contact voltage | 250 V~ |
|-----------------------------------|--------------------------|
| Electrical life (at maximum load) | 1x10 ^s cycles |
| Mechanical life | 1x10 ⁷ cycles |
| Maximum switching capacity | 250 W |

Measurement accuracy

| Phase angle φ | 2 % ± 1 digit |
|---------------------------|---------------|
| Phase current measurement | 1% |
| Phase voltage measurement | 1% |

computer C Wi-Fi

Power factor controller with communications

| CODE | TYPE | Switching unit | Nr steps | Input current |
|---------------|--------------------|----------------|----------|---------------|
| R14831. | computer C6 Wi-Fi | Contactor | 6 | / 5A |
| R148310020000 | computer C6 Wi-Fi | Contactor | 6 | / 5A |
| R14842. | computer C12 Wi-Fi | Contactor | 12 | / 5A |
| R148420020000 | computer C12 Wi-Fi | Contactor | 12 | / 5A |

 $\label{thm:compatible} \mbox{Compatible with Anti Reactive Surveillance System - VAR. Programming via the MyConfig app.}$



Page 3 of 4





Fast power factor regulator

Code: R14831.

Dimensions

Connections





