



## CSB-F-15-230

CSB-F-15-230, Power capacitors with fuse protection

Code: R2361E. (CONSULTAR DISPONIBILIDAD)

- > Fuses (A): 80
- > Cable section (mm<sup>2</sup>): 16
- > kvar (230 V): 15
- > Cut off power: 120 kA
- > Use voltage (V): 230
- > Type of protection: Fuse

### Description

The application of new technologies have allowed CIRCUTOR to reinvent the classic **CS** capacitor.

The spirit of innovation and proprietary technology used during the design of the new **CSB** capacitor have increased the working life of conventional prismatic capacitors by over 60%. This new series has improved all aspects of the previous models, offering our customers a capacitor that is longer lasting, safer and more cost-efficient.

### Application

Its application is mainly based on the compensation of transformers and motors. In general, they are used for the compensation of installations with constant loads.



## CSB-F-15-230

Three-phase power capacitor with fuse protection.

Code: R2361E.

### Specifications

#### AC power supply

Frequency	50 Hz
-----------	-------

#### Electrical characteristics

Permanent overload	1,3 In
Losses (W)	Dielectric: < 0,2 W / kvar Total: < 0,5 W / kvar
Discharge resistance	75 V / 3 min
Surge	10%
Tolerance C	± 10 %
Voltage	230 V
Insulation voltage, circuit	3 / 15 kV

#### Mechanical characteristics

Size (mm) width x height x depth	140 x 381 x 280 (mm)
Envelope	Treated and painted steel in RAL 3005 colour
Torque setting	15 Nm
Cable gauge at current terminals	Power M10
Fastening	Vertical / Horizontal. Minimum distance between condensers 4 cm
Ventilation	Natural or forced depending on the cabinet
Weight (kg)	11,3

#### Environmental characteristics

Protection class	IP 42 with terminal cover
Relative humidity (without condensation)	80%
Working temperature	T° class D: Daily average: 45 °C, annual average: 35 °C, maximum: 55 °C, minimum: -25 °C

#### Standards

Electrical safety, Maximum height (m)	2000
Standards	IEC 60831-1, UNE-EN 60831-1

#### Features / performance

Components	CS capacitor + general NH-00 type protection fuses with high cut-off power
------------	--

#### Protection

Circuit breaker type	Dielectric regeneration Internal fuse Overpressure system Vermiculite
----------------------	---

#### CSB-F



## CSB-F-15-230

Three-phase power capacitor with fuse protection.

Code: R2361E.

Power capacitors with fuse protection, 50 Hz.

CODE	TYPE	kvar (400 V)	kvar (440 V)	Use voltage (V)
<b>440 V, 50 Hz</b>				
R23958.	CSB-F-5-440	4	5	440
R2395A.	CSB-F-7,5-440	6	7,5	440
R2395C.	CSB-F-10-440	8	10	440
R2395D.	CSB-F-12,5-440	10	12,5	440
R2395E.	CSB-F-15-440	12,5	15	440
R2395F.	CSB-F-20-440	17	20	440
R2395G.	CSB-F-25-440	21	25	440
R2395H.	CSB-F-30-440	25	30	440
R2395J.	CSB-F-37,5-440	31	37,5	440
R2395K.	CSB-F-50-440	42	50	440
R2395L.	CSB-F-60-440	50	60	440
R2395P.	CSB-F-75-440	63	75	440
R2395Q.	CSB-F-100-440	80	100	440



## CSB-F-15-230

Three-phase power capacitor with fuse protection.

Code: R2361E.

### Dimensions

