



CSB-M-7,5-230

CSB-M-7,5-230, Power capacitors with circuit breaker protection

Code: R2371A. DESCATALOGADO

- > Cable section (mm²): 6
- > kvar (230 V): 7,5
- > Cut off power: 6 kA
- > Aut.Switch (A): 32
- > Use voltage (V): 230
- > Type of protection: Circuit breaker

Description

The application of new technologies have allowed CIRCUTOR to reinvent the classic **CS** capacitor, manufactured for more than 35 years.

The spirit of innovation and proprietary technology used during the design of the new **CSB** capacitor have increased the working life of conventional prismatic capacitors by over 60%. This new series has improved all aspects of the previous models, offering our customers a capacitor that is longer lasting, safer and more cost-efficient.

Application

Its application is mainly based on the compensation of transformers and motors. In general, they are used for the compensation of installations with constant loads.



CSB-M-7,5-230

Three-phase power capacitor with circuitbreaker protection

Code: R2371A.

Specifications

AC power supply

| | |
|-----------|-------|
| Frequency | 50 Hz |
|-----------|-------|

Electrical characteristics

| | |
|-----------------------------|--|
| Permanent overload | 1,3 In |
| Losses (W) | Dielectric: < 0,2 W / kvar Total: < 0,5 W / kvar |
| Discharge resistance | 75 V / 3 min |
| Surge | 10% |
| Tolerance C | ± 10 % |
| Voltage | 230 V |
| Insulation voltage, circuit | 3 / 15 kV |

Mechanical characteristics

| | |
|----------------------------------|---|
| Size (mm) width x height x depth | 140 x 381 x 280 (mm) |
| Envelope | Treated and painted steel in RAL 3005 colour |
| Fastening | Vertical / Horizontal. Minimum distance between condensers 4 cm |
| Ventilation | Natural or forced depending on the cabinet |
| Weight (kg) | 9,2 |

Environmental characteristics

| | |
|--|--|
| Protection class | IP 42 with terminal cover |
| Relative humidity (without condensation) | 80% |
| Working temperature | T° class D: Daily average: 45 °C, annual average: 35 °C, maximum: 55 °C, minimum: -25 °C |

Standards

| | |
|---------------------------------------|-----------------------------|
| Electrical safety, Maximum height (m) | 2000 |
| Standards | IEC 60831-1, UNE-EN 60831-1 |

Features / performance

| | |
|------------|---|
| Components | CSB capacitor General three-pole circuit breaker protection |
|------------|---|

Protection

| | |
|----------------------|---|
| Circuit breaker type | Dielectric regeneration Internal fuse Overpressure system Vermiculite |
|----------------------|---|

CSB-M

Power capacitors with miniature circuit breaker protection, 50 Hz



CSB-M-7,5-230

Three-phase power capacitor with circuitbreaker protection

Code: R2371A.

| CODE | TYPE | kvar (400 V) | kvar (440 V) | Use voltage (V) |
|----------------|----------------|--------------|--------------|-----------------|
| 440 Vac, 50 Hz | | | | |
| R23948. | CSB-M-5-440 | 4 | 5 | 440 |
| R2394A. | CSB-M-7,5-440 | 6 | 7,5 | 440 |
| R2394C. | CSB-M-10-440 | 8 | 10 | 440 |
| R2394D. | CSB-M-12,5-440 | 10 | 12,5 | 440 |
| R2394E. | CSB-M-15-440 | 12,5 | 15 | 440 |
| R2394F. | CSB-M-20-440 | 17 | 20 | 440 |
| R2394G. | CSB-M-25-440 | 21 | 25 | 440 |
| R2394H. | CSB-M-30-440 | 25 | 30 | 440 |
| R2394J. | CSB-M-37,5-440 | 31 | 37,5 | 440 |
| R2394K. | CSB-M-50-440 | 42 | 50 | 440 |
| R2394L. | CSB-M-60-440 | 50 | 60 | 440 |
| R2394M. | CSB-M-75-440 | 66 | 75 | 440 |



CSB-M-7,5-230

Three-phase power capacitor with circuitbreaker protection

Code: R2371A.

Dimensions

