

CPA-15-440, Fixed capacitors with automatic protection

Code: R24A3D.

- > Cable section (mm2): 16
- > kvar (400 V): 12,5
- > kvar (440 V): 15
- > Cut off power: 50 kA
- > Aut.Switch (A): 63
- > Use voltage (V): 440
- > Type of protection: automatischer Schalter

Description

The **CPA** capacitors with automatic switch protection are fixed compensation units that have been designed for reactive energy compensation purposes in motors and transformers with constant load levels. Including a general protection system with an automatic switch for the capacitor.

Application

Its application is mainly based on the compensation of transformers and motors. In general, they are used for the compensation of installations with constant loads.

Circutor



Fixed capacitors with automatic protection

Code: R24A3D.

Specifications

AC power supply	
Frequency	50 Hz
Electrical characteristics	
Permanent overload	1,3 In
Losses (W)	Dielectric: < 0,2 W / kvar Total: < 0,5 W / kvar
Discharge resistance	75 V / 3 min
Surge	10%
Tolerance C	± 10 %
Voltage	440 V
Insulation voltage, circuit	3 / 15 kV
Mechanical characteristics	
Size (mm) width x height x depth	360 x 814 x 196 (mm)
Envelope	Treated and painted steel in RAL 3005 colour
Fastening	Vertical / Horizontal. Minimum distance between condensers 4 cm
Ventilation	Natural or forced depending on the cabinet
Weight (kg)	10
Environmental characteristics	
Protection class	IP 42 with terminal cover
Relative humidity (without condensation)	80%
Working temperature	Tª class D: Daily average: 45 °C, annual average: 35 °C, maximum: 55 °C, minimum -25 °C
Standards	
Electrical safety, Maximum height (m)	2000
Standards	IEC 60831-1, UNE-EN 60831-1
Features / performance	
Components	CSB capacitor General three-pole circuit breaker protection
Protection	
Circuit breaker type	Dielectric regeneration Internal fuse Overpressure system Vermiculite

CPA

Fixed capacitors with automatic 50-Hz switch protection

Circutor



Fixed capacitors with automatic protection

Code: R24A3D.

R24A3D.CPA-15-44012,515R24A3H.CPA-25-4402125R24A3G.CPA-37,5-4403137,5R24A3J.CPA-50-4404250R24A3K.CPA-60-4405060	440
R24A3G. CPA-37,5-440 31 37,5 R24A3J. CPA-50-440 42 50	
R24A3J. CPA-50-440 42 50	440
	440
R24A3K. CPA-60-440 50 60	440
	440
R24A3L. CPA-75-440 62 75	440
R24A3M. CPA-100-440 83 100	440
R24A3N. CPA-120-440 100 120	440

Cable cross-section for installations with Un= 400 V. The installation company must ensure compliance with the low voltage directive at all times, in accordance with the particularities of each installation and type of cable

Circutor



Fixed capacitors with automatic protection

Code: R24A3D.

Dimensions

×

