

CPA-60-440, Fixed capacitors with automatic protection

Code: R24A3K.

- > Cable section (mm2): 35
- > kvar (400 V): 50
- > kvar (440 V): 60
- > Cut off power: 50 kA
- > Aut.Switch (A): 125
- > Use voltage (V): 440
- > Type of protection: automatischer Schalter

#### Description

The **CPA** capacitors with automatic switch protection are fixed compensation units that have been designed for reactive energy compensation purposes in motors and transformers with constant load levels. Including a general protection system with an automatic switch for the capacitor.

#### Application

Its application is mainly based on the compensation of transformers and motors. In general, they are used for the compensation of installations with constant loads.

## Circutor



Fixed capacitors with automatic protection

Code: R24A3K.

#### Specifications

AC power supply	
Frequency	50 Hz
Electrical characteristics	
Permanent overload	1,3 In
Losses (W)	Dielectric: < 0,2 W / kvar Total: < 0,5 W / kvar
Discharge resistance	75 V / 3 min
Surge	10%
Tolerance C	± 10 %
Voltage	440 V
Insulation voltage, circuit	3 / 15 kV
Mechanical characteristics	
Size (mm) width x height x depth	360 x 814 x 196 (mm)
Envelope	Treated and painted steel in RAL 3005 colour
Fastening	Vertical / Horizontal. Minimum distance between condensers 4 cm
Ventilation	Natural or forced depending on the cabinet
Weight (kg)	18
Environmental characteristics	
Protection class	IP 42 with terminal cover
Relative humidity (without condensation)	80%
Working temperature	Tª class D: Daily average: 45 °C, annual average: 35 °C, maximum: 55 °C, minimum -25 °C
Standards	
Electrical safety, Maximum height (m)	2000
Standards	IEC 60831-1, UNE-EN 60831-1
Features / performance	
Components	CSB capacitor General three-pole circuit breaker protection
Protection	
Circuit breaker type	Dielectric regeneration Internal fuse Overpressure system Vermiculite

CPA

Fixed capacitors with automatic 50-Hz switch protection

Circutor



Fixed capacitors with automatic protection

Code: R24A3K.

R24A3D.CPA-15-44012,515R24A3H.CPA-25-4402125R24A3G.CPA-37,5-4403137,5R24A3J.CPA-50-4404250R24A3K.CPA-60-4405060	440
R24A3G. CPA-37,5-440 31 37,5   R24A3J. CPA-50-440 42 50	
R24A3J. CPA-50-440 42 50	440
	440
R24A3K. CPA-60-440 50 60	440
	440
R24A3L. CPA-75-440 62 75	440
R24A3M. CPA-100-440 83 100	440
R24A3N. CPA-120-440 100 120	440

Cable cross-section for installations with Un= 400 V. The installation company must ensure compliance with the low voltage directive at all times, in accordance with the particularities of each installation and type of cable

# Circutor



Fixed capacitors with automatic protection

Code: R24A3K.

## Dimensions

×

