



CMC-12B+RD+CABLES

CMC-12B+RD+CABLES, Contactor

Code: R281B6.

> Frequency (Hz): 50 / 60

> kvar 220-240V: 6.7

> kvar 400-440-480 V: 12.5

> kvar 500-550V: 12

> kvar 660-690 V: 18

> Dumping resistors: Included

> Coil voltage (Vac): 230

Description

CMC-B series are contactors adjusted for switching single-step or multiple step capacitor banks. They have high operating times and a high electrical endurance that make the most robust and durable contactors.

Application

They are installed in switching single-step or multiple step capacitor banks.







CMC-12B+RD+CABLES

Capacitors contactors

Code: R281B6.

Specifications

50/60 Hz
220 690 V
240/h
18.5 A (400 V)
230 V / 0,85 1,1 Un
200000 cycles
690 1000 V
44.8 x 86 x 107.9 (mm)
0,34
IP 00
5 95 %
-25 +55 °C
-25 +55 °C
-25 +55 °C VDE

CMC-B+RD

Contactors with fast discharge resistor

CODE	TYPE	Frequency (Hz)	kvar 220-240V	kvar 400-440-480 V	kvar 500-550V	kvar 660-690 V
R281B6.	CMC-12B+RD+CABLES	50 / 60	6.7	12.5	12	18
R281B4.	CMC-20B+RD+CABLES	50 / 60	11	20	24	30
R281B8.	CMC-32B+RD+CABLES	50 / 60	14	25	30	35
R281B1.	CMC-40B+RD+CABLES	50 / 60	20	30	35	40
R281B9.	CMC-75B+RD+CABLES	50 / 60	29	50	60	70
R281B3.	CMC-85B+RD+CABLES	50 / 60	32	60	70	80
R281BH.	CMC-150D+RD+CABLES	50 / 60	45	80	100	115







CMC-12B+RD+CABLES

Capacitors contactors

Code: R281B6.



Page 3 of 3