



CLZ-FP-60/21-60Hz-HD

CLZ-FP-60/21-60Hz-HD, Three-phase tubular power capacitor 60 Hz

Code: R2H68K.

- > Terminal: A
- > Frequency (Hz): 60
- > kvar (600 V): 21
- > Cover (opc.): 7
- > Use voltage (V): 600

Description

CLZ-HD (Heavy duty) capacitor range is composed of capacitors with a tubular casing, of the dry-type, covering a wide range of power and voltage ratings, at 50 and 60 Hz. The CLZ-HD capacitors are designed to be installed in installations with extreme working conditions. The design, manufacturing and testing processes guarantee the production of top quality and long lasting capacitors. Those CLZ-HD capacitors offer a new refrigeration technology by means of nitrogen gas*, being a refrigerating system of high benefits, inert and non flammable.

Application

Its application is based on compensation in installations with static or variable loads (capacitor banks). Especially designed to be installed in roughly environments with the most extreme conditions due to its longer life and high temperature resistance.



CLZ-FP-60/21-60Hz-HD

Code: R2H68K.

Specifications

AC power supply

| | |
|-----------|-------|
| Frequency | 60 Hz |
|-----------|-------|

Electrical characteristics

| | |
|-----------------------------|---------------------------------------------------------------------------------------------------------|
| Losses (W) | Dielectric: < 0,2 W / kvar Total: < 0,4 W / kvar |
| Discharge resistance | 50 V / 1 min (0,5 - 30 kvar) 75 V / 3 min (33 - 50 kvar) |
| Surge | 10 % 8h in 24 h 15 % up to 30 min in 24 hours 20 % up to 5 min in 24 hours 30 % up to 1 min in 24 hours |
| Tolerance C | -5 ... +10 % |
| Maximum phase current | 400 x In |
| Maximum transient current | 1,8 In |
| Voltage | 600 V |
| Insulation voltage, circuit | 3 / 8 kV |

Mechanical characteristics

| | |
|----------------------------------|--------------------------------------------|
| Size (mm) width x height x depth | 100 x 276 x 100 (mm) |
| Envelope | Aluminum |
| Fastening | M12 fastening screws earth conductor |
| Ventilation | Natural or forced depending on the cabinet |
| Weight (kg) | 1,6 |

Environmental characteristics

| | |
|------------------------------------------|------------------------------------------------------------------------------------------|
| Protection class | IP 20 / IP 54 with terminal cover (optional) (for models Ø 85, 100, 116 mm) |
| Relative humidity (without condensation) | 95% |
| Installation, location, position. | Vertical / Horizontal. Minimum distance between condensers 2 cm. |
| Working temperature | T° class D: Daily average: 45 °C, annual average: 35 °C, maximum: 65 °C, minimum: -50 °C |

Standards

| | |
|---------------------------------------|-----------------|
| Certifications | VDE 560 |
| Electrical safety, Maximum height (m) | 4000 |
| Standards | IEC 60831-1-1/2 |

Protection

| | |
|----------------------|------------------------------------------|
| Circuit breaker type | Dielectric regeneration Expansion system |
|----------------------|------------------------------------------|

CLZ-FP HD 60Hz

Three-phase tubular power capacitor (Heavy Duty range)



CLZ-FP-60/21-60Hz-HD

Code: R2H68K.

| CODE | TYPE | kvar (230 V) | kvar (240 V) | Use voltage (V) | kvar (400 V) | kvar (440 V) | kvar (460 V) | kvar (480 V) | kvar (525 V) | kvar (600 V) | kvar (660 V) | kvar (690 V) |
|------------------------------------------------|-------------------------|--------------|--------------|-----------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
| Faston terminal, Un = 3 x 240 V / 60 Hz | | | | | | | | | | | | |
| R2H622. | CLZ-FPT-24/2,5-60Hz-HD | 2,3 | 2,5 | 240 | | | | | | | | |
| Terminal block, Un = 3 x 240 V / 60 Hz | | | | | | | | | | | | |
| R2H626. | CLZ-FP-24/5-60Hz-HD | 4,6 | 5 | 240 | | | | | | | | |
| R2H627. | CLZ-FP-24/6,25-60Hz-HD | 5,75 | 6,25 | 240 | | | | | | | | |
| R2H628. | CLZ-FP-24/7,5-60Hz-HD | 6,9 | 7,5 | 240 | | | | | | | | |
| R2H62B. | CLZ-FP-24/10-60Hz-HD | 9,2 | 10 | 240 | | | | | | | | |
| R2H62D. | CLZ-FP-24/12,5-60Hz-HD | 11,5 | 12,5 | 240 | | | | | | | | |
| R2H62E. | CLZ-FP-24/15-60Hz-HD | 13,8 | 15 | 240 | | | | | | | | |
| Faston terminal, Un = 3 x 440 V / 60 Hz | | | | | | | | | | | | |
| R2H641. | CLZ-FPT-44/1,25-60Hz-HD | | | 400 440 | 1 | 1,25 | | | | | | |
| R2H642. | CLZ-FPT-44/2,5-60Hz-HD | | | 400 440 | 2,1 | 2,5 | | | | | | |
| R2H643. | CLZ-FPT-44/3-60Hz-HD | | | 400 440 | 2,5 | 3 | | | | | | |
| R2H644. | CLZ-FPT-44/3,75-60Hz-HD | | | 400 440 | 3,1 | 3,75 | | | | | | |
| R2H646. | CLZ-FPT-44/5-60Hz-HD | | | 400 440 | 4,15 | 5 | | | | | | |
| Terminal block, Un = 3 x 440 V / 60 Hz | | | | | | | | | | | | |
| R2H647. | CLZ-FP-44/6,25-60Hz-HD | | | 400 440 | 5,2 | 6,25 | | | | | | |
| R2H648. | CLZ-FP-44/7,5-60Hz-HD | | | 400 440 | 6,2 | 7,5 | | | | | | |
| R2H64B. | CLZ-FP-44/10-60Hz-HD | | | 400 440 | 8,3 | 10 | | | | | | |
| R2H64D. | CLZ-FP-44/12,5-60Hz-HD | | | 400 440 | 10,3 | 12,5 | | | | | | |
| R2H64E. | CLZ-FP-44/15-60Hz-HD | | | 400 440 | 12,4 | 15 | | | | | | |
| R2H64J. | CLZ-FP-44/20-60Hz-HD | | | 400 440 | 16,5 | 20 | | | | | | |
| R2H64L. | CLZ-FP-44/25-60Hz-HD | | | 400 440 | 20,7 | 25 | | | | | | |
| R2H64N. | CLZ-FP-44/30-60Hz-HD | | | 400 440 | 24,8 | 30 | | | | | | |
| R2H64R. | CLZ-FP-44/40-60Hz-HD | | | 400 440 | 33,1 | 40 | | | | | | |
| R2H64S. | CLZ-FP-44/50-60Hz-HD | | | 400 440 | 41,3 | 50 | | | | | | |
| Faston terminal, Un = 3 x 480 V / 60 Hz | | | | | | | | | | | | |
| R2H762. | CLZ-FPT-48/2,5-60Hz-HD | | | 480 | | | 2,3 | 2,5 | | | | |
| R2H766. | CLZ-FPT-48/5-60Hz-HD | | | 480 | | | 4,6 | 5 | | | | |
| R2H767. | CLZ-FPT-48/6,25-60Hz-HD | | | 480 | | | 5,75 | 6,25 | | | | |
| R2H768. | CLZ-FPT-48/7,5-60Hz-HD | | | 480 | | | 6,9 | 7,5 | | | | |
| Terminal block, Un = 3 x 480 V / 60 Hz | | | | | | | | | | | | |
| R2H66B. | CLZ-FP-48/10-60Hz-HD | | | 480 | | | 9,2 | 10 | | | | |
| R2H66D. | CLZ-FP-48/12,5-60Hz-HD | | | 480 | | | 11,5 | 12,5 | | | | |
| R2H66E. | CLZ-FP-48/15-60Hz-HD | | | 480 | | | 13,8 | 15 | | | | |
| R2H66J. | CLZ-FP-48/20-60Hz-HD | | | 480 | | | 18,4 | 20 | | | | |
| R2H66L. | CLZ-FP-48/25-60Hz-HD | | | 480 | | | 23 | 25 | | | | |
| R2H66N. | CLZ-FP-48/30-60Hz-HD | | | 480 | | | 27,6 | 30 | | | | |
| R2H66R. | CLZ-FP-48/40-60Hz-HD | | | 480 | | | 36,75 | 40 | | | | |
| R2H66S. | CLZ-FP-48/50-60Hz-HD | | | 480 | | | 46 | 50 | | | | |
| Faston terminal, Un = 3 x 525 V / 60 Hz | | | | | | | | | | | | |
| R2H772. | CLZ-FPT-52/2,5-60Hz-HD | | | 525 | | | | 2,1 | 2,5 | | | |
| R2H776. | CLZ-FPT-52/5-60Hz-HD | | | 525 | | | | 4,2 | 5 | | | |



CLZ-FP-60/21-60Hz-HD

Code: R2H68K.

| CODE | TYPE | kvar (230 V) | kvar (240 V) | Use voltage (V) | kvar (400 V) | kvar (440 V) | kvar (460 V) | kvar (480 V) | kvar (525 V) | kvar (600 V) | kvar (660 V) | kvar (690 V) |
|------------------------------------------------|-------------------------|--------------|--------------|-----------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
| R2H777. | CLZ-FPT-52/6,25-60Hz-HD | | | 525 | | | | 5,2 | 6,25 | | | |
| R2H778. | CLZ-FPT-52/7,5-60Hz-HD | | | 525 | | | | 6,25 | 7,5 | | | |
| Terminal block, Un = 3 x 525 V / 60 Hz | | | | | | | | | | | | |
| R2H67A. | CLZ-FP-52/8,5-60Hz-HD | | | 525 | | | | 7,1 | 8,5 | | | |
| R2H67B. | CLZ-FP-52/10-60Hz-HD | | | 525 | | | | 8,4 | 10 | | | |
| R2H67C. | CLZ-FP-52/11,5-60Hz-HD | | | 525 | | | | 9,6 | 11,5 | | | |
| R2H67D. | CLZ-FP-52/12,5-60Hz-HD | | | 525 | | | | 10,5 | 12,5 | | | |
| R2H67E. | CLZ-FP-52/15-60Hz-HD | | | 525 | | | | 12,5 | 15 | | | |
| R2H67I. | CLZ-FP-52/17-60Hz-HD | | | 525 | | | | 14,2 | 17 | | | |
| R2H67J. | CLZ-FP-52/20-60Hz-HD | | | 525 | | | | 16,7 | 20 | | | |
| R2H67K. | CLZ-FP-52/22,5-60Hz-HD | | | 525 | | | | 18,8 | 22,5 | | | |
| R2H67L. | CLZ-FP-52/25-60Hz-HD | | | 525 | | | | 20,9 | 25 | | | |
| R2H67N. | CLZ-FP-52/30-60Hz-HD | | | 525 | | | | 25 | 30 | | | |
| R2H67P. | CLZ-FP-52/34-60Hz-HD | | | 525 | | | | 28,4 | 34 | | | |
| R2H67R. | CLZ-FP-52/40-60Hz-HD | | | 525 | | | | 33,4 | 40 | | | |
| Faston terminal, Un = 3 x 600 V / 60 Hz | | | | | | | | | | | | |
| R2H782. | CLZ-FPT-60/2,5-60Hz-HD | | | 600 | | | | | | 2,5 | | |
| R2H786. | CLZ-FPT-60/5-60Hz-HD | | | 600 | | | | | | 5 | | |
| R2H787. | CLZ-FPT-60/6,25-60Hz-HD | | | 600 | | | | | | 6,25 | | |
| R2H788. | CLZ-FPT-60/7,5-60Hz-HD | | | 600 | | | | | | 7,5 | | |
| Terminal block, Un = 3 x 600 V / 60 Hz | | | | | | | | | | | | |
| R2H68A. | CLZ-FP-60/10-60Hz-HD | | | 600 | | | | | | 10 | | |
| R2H68B. | CLZ-FP-60/12,5-60Hz-HD | | | 600 | | | | | | 12,5 | | |
| R2H68E. | CLZ-FP-60/15-60Hz-HD | | | 600 | | | | | | 15 | | |
| R2H68I. | CLZ-FP-60/17,5-60Hz-HD | | | 600 | | | | | | 17,5 | | |
| R2H68J. | CLZ-FP-60/20-60Hz-HD | | | 600 | | | | | | 20 | | |
| R2H68K. | CLZ-FP-60/21-60Hz-HD | | | 600 | | | | | | 21 | | |
| R2H68L. | CLZ-FP-60/25-60Hz-HD | | | 600 | | | | | | 25 | | |
| R2H68N. | CLZ-FP-60/30-60Hz-HD | | | 600 | | | | | | 30 | | |
| R2H68P. | CLZ-FP-60/34,5-60Hz-HD | | | 600 | | | | | | 34,5 | | |
| Faston terminal, Un = 3 x 690 V / 60 Hz | | | | | | | | | | | | |
| R2H792. | CLZ-FPT-69/2,5-60Hz-HD | | | 690 | | | | | | | 2,3 | 2,5 |
| R2H796. | CLZ-FPT-69/5-60Hz-HD | | | 690 | | | | | | | 4,6 | 5 |
| R2H798. | CLZ-FPT-69/7,5-60Hz-HD | | | 690 | | | | | | | 6,9 | 7,5 |
| Terminal block, Un = 3 x 690 V / 60 Hz | | | | | | | | | | | | |
| R2H69B. | CLZ-FP-69/10-60Hz-HD | | | 690 | | | | | | 9,15 | 10 | |
| R2H69D. | CLZ-FP-69/12,5-60Hz-HD | | | 690 | | | | | | 11,4 | 12,5 | |
| R2H69E. | CLZ-FP-69/15-60Hz-HD | | | 690 | | | | | | 13,7 | 15 | |
| R2H69J. | CLZ-FP-69/20-60Hz-HD | | | 690 | | | | | | 18,3 | 20 | |
| R2H69L. | CLZ-FP-69/25-60Hz-HD | | | 690 | | | | | | 22,9 | 25 | |
| R2H69N. | CLZ-FP-69/30-60Hz-HD | | | 690 | | | | | | 27,5 | 30 | |
| R2H69R. | CLZ-FP-69/40-60Hz-HD | | | 690 | | | | | | 36,6 | 40 | |
| R2H69S. | CLZ-FP-69/50-60Hz-HD | | | 690 | | | | | | 45,75 | 50 | |



CLZ-FP-60/21-60Hz-HD

Code: R2H68K.

All models are of the inert gas type, except for those with a 63.5 mm diameter and 136x355 mm size. The dimensions (dxh) are shown for the tube only. Please consult the dimensions drawing at the end of this section for more information about the actual dimensions. Terminal: maximum cross-section of type A cables: 16 mm², type B: 25 mm², type C: 35 mm², F: Faston 6.3x0.8 mm and 12 A maximum current.



CLZ-FP-60/21-60Hz-HD

Code: R2H68K.

Dimensions

