



OPTIM 1-2,5-440

OPTIM 1-2,5-440, Capacitor bank

Code: R3Q631EN00000 DESCATALOGADO

- > Cable section (mm²): 6
- > Nr steps: 1
- > kvar (400 V): 2
- > kvar (440 V): 2,5
- > Aut.Switch (A): Included
- > Man.Switch (A): -
- > Composition: 1 x 2,5
- > Use voltage (V): 440
- > Mounting: Wall-mounted

Description

The regulated capacitors of the OPTIM 1 / OPTIM 1A / OPTIM 1M series are power factor compensation units operated by a computer one (OPTIM 1 / OPTIM 1A) or computer one m (OPTIM 1M) reactive relay.

Application

Their simple installation, high-technology and robustness make OPTIM 1 / OPTIM 1A / OPTIM 1M regulated capacitors an ideal compact unit for compensating reactive energy in low power installations or loads where the load levels are not subject to major fluctuations such as:

- Small businesses
- Restaurants
- Lifts
- Irrigation pumps
- etc.



OPTIM 1-2,5-440

Capacitors banks

Code: R3Q631EN00000

Specifications

AC power supply

Frequency	50 Hz
-----------	-------

Electrical characteristics

Losses (W)	< 0,5 W/kvar
Discharge resistance	75 V / 3 min
Surge	10 % 8 h over 24 h 15 % up to 15 min over 24 hours 20 % up to 5 min over 24 hours 30 % up to 1 min over 24 hours
Manoeuvre voltage	Contactors: 230 V
Reinforcement voltage	440 V
Tolerance C	-5% / 10 %
Voltage	400 V (other voltages on request)

Mechanical characteristics

Size (mm) width x height x depth	215 x 500 x 166 (mm)
Envelope	Thermoplastic. RAL 7035
Thermal management	Natural or forced according to options
Fastening	Vertical
Weight (kg)	3,5

Environmental characteristics

Protection class	IP 21
Relative humidity (without condensation)	80%
Working temperature	T ^a class D: Daily average: 45 °C, annual average: 35 °C, maximum: 55 °C, minimum: -50 °C

Current measurement circuit

Permanent overload	1,3 I _n
Transformation ratio	I _n / 0,25 A

Standards

Electrical safety, Maximum height (m)	1000 máx. (para altitud mayor prever siempre ventilación forzada)
Standards	IEC 60831-1, IEC 61921, IEC 60439

Features / performance

Optional	Other frequencies, consult.
----------	-----------------------------



OPTIM 1-2,5-440

Capacitors banks

Code: R3Q631EN00000

Dimensions

