

### ACF-25-230

ACF-25-230, Power capacitor with contactor and fuses

#### Code: R3S151. DESCATALOGADO

- > Fuses (A): 125
- > Cable section (mm2): 35
- > In (A): 63
- > kvar (230 V): 25
- > Cut off power: 120 kA
- > Use voltage (V): 230
- > Type of protection: contactor and fuse

### Description

The fixed capacitors of the ACF series are single-step units that have been designed for Power factor correction procedures under constant load.

### Application

Its application is mainly focused on the compensation of motors, transformers and installations under constant load, providing a signal that connects to the capacitor with a contactor switching operation.

# Circutor



### ACF-25-230

CS Capacitor with contactor and fuses

Code: R3S151.

### Specifications

Discharge resistance	75 V / 3 min
Surge	10 % 8 h over 24 h 15 % up to 15 min over 24 hours 20 % up to 5 min over 24 hours 30 % up to 1 min over 24 hours
Manoeuvre voltage	Contactors: 230 V
Reinforcement voltage	400 V
Tolerance C	± 10 % sobre la capidad
Voltage	230 V
Insulation voltage, circuit	3 kV
Mechanical characteristics	
Size (mm) width x height x depth	360 x 1004 x 196 (mm)
Envelope	RAL 7035 Grey / RAL 3005 Garnet
Fastening	Vertical
Ventilation	Natural
Weight (kg)	21
Environmental characteristics	
Protection class	IP 21
Relative humidity (without condensation)	80%
Working temperature	T° class D: Daily average: 45 °C, annual average: 35 °C, maximum: 50 °C, minimun -25 °C
Standards	
	VDE 560
Certifications	
Certifications Electrical safety, Maximum height (m)	2000
Electrical safety, Maximum height (m)	2000
Electrical safety, Maximum height (m) Standards	2000
Electrical safety, Maximum height (m) Standards Current measurement circuit	2000 IEC 60831-1, IEC 70/7, UNE-EN 20827, UNE-EN 20010, BS 1650

Switch and cable cross-section for installations with Un= 400 V. The installation company must ensure compliance with the low voltage directive at all times, in accordance with the particularities of each installation and type of cable

Circutor



## ACF-25-230

CS Capacitor with contactor and fuses

Code: R3S151.

## Dimensions

×

