



EMK8-800-440

EMK8-800-440

Code: R47455. DESCATALOGADO

- > Static capacitor bank
- > Cable section (mm²): 3 x 185
- > kvar (400 V): 661
- > kvar (440 V): 800
- > Aut.Switch (A): 1600
- > Man.Switch (A): 1600
- > Composition: 8 x 100
- > Use voltage (V): 440

Description

The **EMK**-series capacitor banks have been designed for power factor correction in networks with fluctuating loads.

The power variations are relatively quick (measured in milliseconds) and the operation is thus carried out by thyristors, which are connected to a voltage controller board, so that the connection and disconnection of the capacitor is carried out with zero voltage difference.

Transients are prevented between the connection and disconnection of the steps, obtaining an immediate response to the load fluctuations.

Application

The most common application is with individual loads or in installations where a quick compensation response is needed (for ex., welding units, motors for lifting units, lifts, etc.)



EMK8-800-440

Automatic capacitor banks with static system

Code: R47455.

Specifications

Mechanical characteristics

Size (mm) width x height x depth	1530 x 1805 x 575 (mm)
Weight (kg)	200

Switch and cable cross-section for installations with $U_n = 400$ V. The installation company must ensure compliance with the low voltage directive at all times, in accordance with the particularities of each installation and type of cable