



## OPTIM FRF-25-440

---

OPTIM FRF-25-440, Fixed capacitor with armonic filter

Code: R5X350.

- > Cable section (mm<sup>2</sup>): 10
- > kvar (400 V): 21
- > kvar (440 V): 25
- > Use voltage (V): 440

### Description

---

The **FRF / FRM** Series capacitor banks with detuned filters have been designed for power compensation purposes in motors and transformers with a constant load level, a high content of harmonics and where there is a risk of resonance. Including:

- **FRF**: general protection with NH-00 fuses with a high rupture power (HRP) for the capacitor.
- **FRM**: general circuit breaker protection for the capacitor.

### Application

---

Its application is mainly based on the compensation of transformers and motors. In general, it is used for the compensation of installations under constant loads and where there is a high content of harmonics in the network.



## OPTIM FRF-25-440

Fixed capacitor with rejection reactance  $p = 7\%$

Code: R5X350.

### Specifications

#### Electrical characteristics

Reinforcement voltage	440 V
Tolerance C	$\pm 10\%$

#### Mechanical characteristics

Size (mm) width x height x depth	650 x 1060 x 420 (mm)
Weight (kg)	78

#### Environmental characteristics

Relative humidity (without condensation)	80%
--	-----

#### Standards

Electrical safety, Maximum height (m)	2000 m
---------------------------------------	--------



## OPTIM FRF-25-440

Fixed capacitor with rejection reactance  $p = 7\%$

Code: R5X350.

### OPTIM FRF

Fixed capacitors with detuned reactor of P = 7% (fres=189 Hz), 50 Hz

CODE	TYPE	kvar (400 V)	kvar (440 V)	Cable section (mm <sup>2</sup> )
R5X350.	OPTIM FRF-25-440	21	25	10
R5X370.	OPTIM FRF-37,5-440	31	37,5	16
R5X380.	OPTIM FRF-50-440	42	50	25
R5X390.	OPTIM FRF-60-440	50	60	35
R5X3A0.	OPTIM FRF-75-440	62	75	50
R5X3B0.	OPTIM FRF-100-440	83	100	70

See CFB capacitor and RZ /RBZ reactor components in the Low Voltage Capacitor and Reactor Section. Cable cross-section for installations with  $U_n = 400$  V. The installation company must ensure compliance with the low voltage directive at all times, in accordance with the particularities of each installation and type of cable



## OPTIM FRF-25-440

Fixed capacitor with rejection reactance  $p = 7\%$

Code: R5X350.

### Dimensions

