

## FAR5-Q6-262,5-400

FAR5-Q6-262,5-400 ( 37,5 + 3x75 )

Code: R7C105. **DESCATALOGADO** 

> hybrid filter

Hybrid absorption filters

## Description

FAR-Q filters have been designed for Power factor correction purposes in networks with an average harmonic distortion, i.e., in networks where the objective is to improve the power factor and filter harmonics at the same time. Contactor switching.







## FAR5-Q6-262,5-400

Hybrid absorption filter

Code: R7C105.

## **Specifications**

AC power supply	
Frequency	50 / 60 Hz
Nominal voltage	400 Vca /480 Vca F-F
Mechanical characteristics	
Size (mm) width x height x depth	1100 x 1900 x 650 (mm)
Envelope	Treated and painted steel. Frame RAL 1013 / Doors RAL 3005
Thermal management	Natural
Fastening	On the ground
Weight (kg)	460
Environmental characteristics  Protection class	IP 20
Installation, location, position.	Inside
Ambient temperature	-10 +45 °C
Electrical characteristics	
Resonance frequency (fh)	1,1 fh
Insulation voltage, circuit	2 kV (inductancia) / 3 kV (aislamiento a masa del condensador)
Standards	
Standards	IEC 61642, IEC 60831, IEC 60439, IEC 60289, IEC 60664

Maximum current in the installation

