



## LCL-TH 35-12A-400

LCL-TH 35-12A-400

Code: R7K106. DESCATALOGADO

> Filter

### Specifications

#### AC power supply

|                 |   |
|-----------------|---|
| Frequency       | 60 Hz   |
| Nominal voltage | 400 Vca / 480 Vca F-F (otras tensiones, bajo demanda) |

#### Mechanical characteristics

|                                  |  |
|----------------------------------|--|
| Size (mm) width x height x depth | 365 x 570 x 217 (mm)                                       |
| Envelope                         | Treated and painted steel. Frame RAL 1013 / Doors RAL 3005 |
| Fastening                        | On the ground  |

#### Environmental characteristics

|  |         |
|--|---------|
| Protection class                         | IP 20   |
| Relative humidity (without condensation) | 80%     |
| Installation, location, position.        | Inside  |
| Operating temperature                    | + 35 °C |

#### Electrical characteristics

|                              |            |
|------------------------------|------------|
| Nominal current voltage drop | < 2 %      |
| LC load current (RMS)        | 12 A       |
| Residual current THD         | Approx. 8% |

#### Current measurement circuit

|                    |  |
|--------------------|--|
| Allowable overload | 1,5 I <sub>c</sub> (≤ 1 min.) + I <sub>c</sub> (≤ 5 min.) (at maximum operating temperature) |
|--------------------|--|

#### Standards

|           |   |
|-----------|---|
| Standards | UNE-EN 60439 , UNE-EN60831 , IEC 61000-6-3 , IEC 61000-6-4, Class A |
|-----------|---|