



LCL-TH 35-12A-400

LCL-TH 35-12A-400

Code: R7K106. DESCATALOGADO

> Filter

Specifications

AC power supply

| | |
|-----------------|---|
| Frequency | 60 Hz |
| Nominal voltage | 400 Vca / 480 Vca F-F (otras tensiones, bajo demanda) |

Mechanical characteristics

| | |
|----------------------------------|--|
| Size (mm) width x height x depth | 365 x 570 x 217 (mm) |
| Envelope | Treated and painted steel. Frame RAL 1013 / Doors RAL 3005 |
| Fastening | On the ground |

Environmental characteristics

| | |
|--|---------|
| Protection class | IP 20 |
| Relative humidity (without condensation) | 80% |
| Installation, location, position. | Inside |
| Operating temperature | + 35 °C |

Electrical characteristics

| | |
|------------------------------|------------|
| Nominal current voltage drop | < 2 % |
| LC load current (RMS) | 12 A |
| Residual current THD | Approx. 8% |

Current measurement circuit

| | |
|--------------------|--|
| Allowable overload | 1,5 Ic (≤ 1 min.) + Ic (≤ 5 min.) (at maximum operating temperature) |
|--------------------|--|

Standards

| | |
|-----------|---|
| Standards | UNE-EN 60439 , UNE-EN60831 , IEC 61000-6-3 , IEC 61000-6-4, Class A |
|-----------|---|