



VC-6Z44ED 6,6kV 220V

VC-6Z44ED 6,6kV 220V, MV contactor

Code: R80921.

- > Max. Current (A): 3 x 400
- > Power supply (Vac): 220 Vac
- > Max. voltage: 6,6 kVca

Description

The LVC contactor is a vacuum contactor prepared to control inductive and capacitive loads.

Application

The LVC contactor has been specially designed for industrial applications that require a large number of switching operations. In particular, the loads from motors and capacitors. The LVC vacuum contactor is ideal for the switching operations of capacitor banks between 3.3 and 6.6 kV. Its general features are as follows:

- Interrupting methods, vacuum
- Total control of the electric arc in capacitive switching operations
- Very long working life
- Heavy insulation of the set, composed of three independent vacuum poles, assembled on an insulating structure
- Small size
- Light unit, greatly optimised weight
- Easy to maintain.



VC-6Z44ED 6,6kV 220V

Three-phase contactor for MV capacitors

Code: R80921.

Specifications

Electrical characteristics

Frequency	50 ... 60 Hz
Interrupting power	4 kA
Nominal current I _n (A)	400 A
Manoeuvre voltage	220 Vac / 110 Vdc (on request)
Voltage	6,6 kV

Mechanical characteristics

Size (mm) width x height x depth	353 x 398.6 x 247 (mm)
Weight (kg)	35

Standards

Standards	IEC 60470
-----------	-----------

LVC

Three-phase contactor for MV capacitors

CODE	TYPE	Max. Current (A)	Power supply (Vac)	Max. voltage	weight (kg)
R80921.	VC-6Z44ED 6,6kV 220V	3 x 400	220 Vac	6,6 kVca	35
R809210010000	VC-6Z44ED 6,6kV 110V	3 x 400	110 Vdc	6,6 kVca	35



VC-6Z44ED 6,6kV 220V

Three-phase contactor for MV capacitors

Code: R80921.

Dimensions

