



## CHV-M 100/3,81

CHV-M 100/3,81

Code: R8A1000003810 (CONSULTAR DISPONIBILIDAD)

> MV capacitor

### Description

**CHV** medium-voltage capacitor, made up of different basic capacitive elements.

These basic units are connected in series and parallel with the purpose of obtaining the power at the necessary voltage.

All the elements are protected by an internal fuse. This fuse is disconnected if a fault is detected, isolating only the basic unit that has been damaged. Internal fuse protection ensures greater system safety and service continuity.

### Application

**CHV-M** capacitors are used to build static and automatic MV capacitor banks.

We will vary the number of capacitors in parallel and/or in series depending on the power and voltage required. The stainless-steel box of the **CHV** capacitor makes it a versatile product that can be used in indoor and outdoor applications.



# CHV-M 100/3,81

Single-phase capacitor (indoor and outdoor use)

Code: R8A1000003810

## Specifications

|                  |            |
|------------------|------------|
| Isolators        |            |
| Material         | Porcelain  |
| Insulation level | 20/60 kV   |
| Pollution level  | 16 mm / kV |

|                            |                                                                                                 |
|----------------------------|-------------------------------------------------------------------------------------------------|
| Electrical characteristics |                                                                                                 |
| Losses (W)                 | ≤ 0,15 W / kvar                                                                                 |
| Power                      | 100 kvar                                                                                        |
| Discharge resistance       | Location: Indoor Discharge time: ≤ 10 minutes Residual voltage: ≤ 75 V                          |
| Surge                      | 1.1 A 12 h in 24 hours 1.15 A 30 min in 24 hours 1.2 A 5 min in 24 hours 1.30 1 min in 24 hours |
| Voltage                    | 3810 V                                                                                          |

|                                  |                                                                                                                               |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Mechanical characteristics       |                                                                                                                               |
| Size (mm) width x height x depth | 350 x 537 x 160 (mm)                                                                                                          |
| Material                         | Dielectric: Rough polypropylene film Electrode: Laser-cut aluminium foil Impregnating oil: SAS-40E or M/DBT (PCB-free)        |
| Envelope                         | Stainless steel painted RAL 7035. With 2 wings for fixing to the frame to avoid mechanical stress on the porcelain terminals. |
| Fastening                        | Horizontal or vertical                                                                                                        |
| Weight (kg)                      | 21,9                                                                                                                          |

|                                   |                  |
|-----------------------------------|------------------|
| Environmental characteristics     |                  |
| Installation, location, position. | Indoor / Outdoor |

|           |                          |
|-----------|--------------------------|
| Standards |                          |
| Standards | IEC 60871-1, IEC 60871-5 |

**CHV-M**  
Single-phase MV power capacitors (indoor and outdoor use)

| CODE                           | TYPE           | Q (kvar) | Un (V) | BIL (kV) | w x h x d       | weight (kg) |
|--------------------------------|----------------|----------|--------|----------|-----------------|-------------|
| BIL 20/60 kV (50 Hz) - 3,81 kV |                |          |        |          |                 |             |
| R8A0500003815                  | CHV-M 50/3,81  | 50       | 3810   | 20/60    | 350 x 487 x 160 | 18,2        |
| R8A075000381E                  | CHV-M 75/3,81  | 75       | 3810   | 20/60    | 350 x 487 x 160 | 18,5        |
| R8A100000381E                  | CHV-M 100/3,81 | 100      | 3810   | 20/60    | 350 x 537 x 160 | 21,9        |
| R8A150000381E                  | CHV-M 150/3,81 | 150      | 3810   | 20/60    | 350 x 637 x 160 | 29,1        |
| R8A167000381E                  | CHV-M 167/3,81 | 167      | 3810   | 20/60    | 350 x 637 x 160 | 29,3        |
| R8A200000381E                  | CHV-M 200/3,81 | 200      | 3810   | 20/60    | 350 x 697 x 160 | 33,5        |



# CHV-M 100/3,81

Single-phase capacitor (indoor and outdoor use)

Code: R8A1000003810

| CODE                            | TYPE           | Q (kvar) | Un (V) | BIL (kV) | w x h x d        | weight (kg) |
|---------------------------------|----------------|----------|--------|----------|------------------|-------------|
| R8A250000381E                   | CHV-M 250/3,81 | 250      | 3810   | 20/60    | 350 x 867 x 160  | 44,8        |
| R8A300000381E                   | CHV-M 300/3,81 | 300      | 3810   | 20/60    | 350 x 867 x 160  | 45,8        |
| R8A333000381E                   | CHV-M 333/3,81 | 333      | 3810   | 20/60    | 350 x 957 x 160  | 52,3        |
| R8A400000381E                   | CHV-M 400/3,81 | 400      | 3810   | 20/60    | 350 x 927 x 175  | 55,3        |
| R8A500000381E                   | CHV-M 500/3,81 | 500      | 3810   | 20/60    | 350 x 1097 x 175 | 68,3        |
| BIL 28/75 kV (50 Hz) - 6,35 kV  |                |          |        |          |                  |             |
| R8B0500006355                   | CHV-M 50/6,35  | 50       | 3810   | 20/60    | 350 x 487 x 160  | 17,9        |
| R8B0750006355                   | CHV-M 75/6,35  | 75       | 3810   | 20/60    | 350 x 537 x 160  | 21,8        |
| R8B1000006355                   | CHV-M 100/6,35 | 100      | 6350   | 28/75    | 350 x 537 x 160  | 21,8        |
| R8B150000635E                   | CHV-M 150/6,35 | 150      | 6350   | 28/75    | 350 x 637 x 160  | 28,6        |
| R8B167000635E                   | CHV-M 167/6,35 | 167      | 6350   | 28/75    | 350 x 637 x 160  | 29,1        |
| R8B200000635E                   | CHV-M 200/6,35 | 200      | 6350   | 28/75    | 350 x 697 x 160  | 33,2        |
| R8B250000635E                   | CHV-M 250/6,35 | 250      | 6350   | 28/75    | 350 x 757 x 160  | 37,8        |
| R8B300000635E                   | CHV-M 300/6,35 | 300      | 6350   | 28/75    | 350 x 867 x 160  | 45,3        |
| R8B333000635E                   | CHV-M 333/6,35 | 333      | 6350   | 28/75    | 350 x 857 x 175  | 49,4        |
| R8B400000635E                   | CHV-M 400/6,35 | 400      | 6350   | 28/75    | 350 x 927 x 175  | 54,5        |
| R8B500000635E                   | CHV-M 500/6,35 | 500      | 6350   | 28/75    | 350 x 1067 x 175 | 65,6        |
| R8B600000635E                   | CHV-M 600/6,35 | 600      | 6350   | 28/75    | 350 x 1247 x 175 | 79,2        |
| R8B750000635E                   | CHV-M 750/6,35 | 750      | 6350   | 28/75    | 350 x 1217 x 200 | 90,4        |
| BIL 38/95 kV (50 Hz) - 9,53 kV  |                |          |        |          |                  |             |
| R8C0500009535                   | CHV-M 50/9,53  | 50       | 9530   | 38/95    | 350 x 530 x 160  | 19,5        |
| R8C0750009535                   | CHV-M 75/9,53  | 75       | 9530   | 38/95    | 350 x 530 x 160  | 20,2        |
| R8C1000009535                   | CHV-M 100/9,53 | 100      | 9530   | 38/95    | 350 x 580 x 160  | 23,6        |
| R8C1500009535                   | CHV-M 150/9,53 | 150      | 9530   | 38/95    | 350 x 680 x 160  | 31          |
| R8C1670009535                   | CHV-M 167/9,53 | 167      | 9530   | 38/95    | 350 x 740 x 160  | 34,9        |
| R8C2000009535                   | CHV-M 200/9,53 | 200      | 9530   | 38/95    | 350 x 740 x 160  | 35,4        |
| R8C2500009535                   | CHV-M 250/9,53 | 250      | 9530   | 38/95    | 350 x 910 x 160  | 46,9        |
| R8C300000953E                   | CHV-M 300/9,53 | 300      | 9530   | 38/95    | 350 x 910 x 160  | 48          |
| R8C333000953E                   | CHV-M 333/9,53 | 333      | 9530   | 38/95    | 350 x 1000 x 160 | 54,7        |
| R8C400000953E                   | CHV-M 400/9,53 | 400      | 9530   | 38/95    | 350 x 1000 x 175 | 59,7        |
| R8C500000953E                   | CHV-M 500/9,53 | 500      | 9530   | 38/95    | 350 x 1140 x 175 | 71          |
| R8C600000953E                   | CHV-M 600/9,53 | 600      | 9530   | 38/95    | 350 x 1290 x 175 | 83,1        |
| R8C750000953E                   | CHV-M 750/9,53 | 750      | 9530   | 38/95    | 350 x 1257 x 200 | 90,4        |
| BIL 50/125 kV (50 Hz) - 12,7 kV |                |          |        |          |                  |             |
| R8D0500012705                   | CHV-M 50/12,7  | 50       | 12700  | 50/125   | 350 x 615 x 160  | 19,7        |
| R8D0750012705                   | CHV-M 75/12,7  | 75       | 12700  | 50/125   | 350 x 665 x 160  | 23,4        |
| R8D1000012705                   | CHV-M 100/12,7 | 100      | 12700  | 50/125   | 350 x 715 x 160  | 26,8        |
| R8D1500012705                   | CHV-M 150/12,7 | 150      | 12700  | 50/125   | 350 x 765 x 160  | 31,2        |
| R8D1670012705                   | CHV-M 167/12,7 | 167      | 12700  | 50/125   | 350 x 825 x 160  | 35,1        |



# CHV-M 100/3,81

Single-phase capacitor (indoor and outdoor use)

Code: R8A1000003810

| CODE                             | TYPE            | Q (kvar) | Un (V) | BIL (kV) | w x h x d        | weight (kg) |
|----------------------------------|-----------------|----------|--------|----------|------------------|-------------|
| R8D2000012705                    | CHV-M 200/12,7  | 200      | 12700  | 50/125   | 350 x 885 x 160  | 39,2        |
| R8D2500012705                    | CHV-M 250/12,7  | 250      | 12700  | 50/125   | 350 x 995 x 160  | 47          |
| R8D3000012705                    | CHV-M 300/12,7  | 300      | 12700  | 50/125   | 350 x 995 x 160  | 48,1        |
| R8D3330012705                    | CHV-M 333/12,7  | 333      | 12700  | 50/125   | 350 x 1055 x 175 | 56,9        |
| R8D4000012705                    | CHV-M 400/12,7  | 400      | 12700  | 50/125   | 350 x 1085 x 175 | 59,6        |
| R8D500001270E                    | CHV-M 500/12,7  | 500      | 12700  | 50/125   | 350 x 1225 x 175 | 70,9        |
| R8D600001270E                    | CHV-M 600/12,7  | 600      | 12700  | 50/125   | 350 x 1375 x 175 | 83          |
| R8D750001270E                    | CHV-M 750/12,7  | 750      | 12700  | 50/125   | 350 x 1405 x 200 | 98,8        |
| BIL 70/170 kV (50 Hz) - 19,05 kV |                 |          |        |          |                  |             |
| R8E0500019055                    | CHV-M 50/19,05  | 50       | 19050  | 70/170   | 350 x 644 x 160  | 23,3        |
| R8E0750019055                    | CHV-M 75/19,05  | 75       | 19050  | 70/170   | 350 x 644 x 160  | 23,6        |
| R8E1000019055                    | CHV-M 100/19,05 | 100      | 19050  | 70/170   | 350 x 694 x 160  | 27          |
| R8E1500019055                    | CHV-M 150/19,05 | 150      | 19050  | 70/170   | 350 x 804 x 160  | 35          |
| R8E1670019055                    | CHV-M 167/19,05 | 167      | 19050  | 70/170   | 350 x 804 x 160  | 35,3        |
| R8E2000019055                    | CHV-M 200/19,05 | 200      | 19050  | 70/170   | 350 x 864 x 160  | 39,4        |
| R8E2500019055                    | CHV-M 250/19,05 | 250      | 19050  | 70/170   | 350 x 964 x 175  | 50,8        |
| R8E3000019055                    | CHV-M 300/19,05 | 300      | 19050  | 70/170   | 350 x 1034 x 175 | 56,5        |
| R8E3330019055                    | CHV-M 333/19,05 | 333      | 19050  | 70/170   | 350 x 1034 x 175 | 57,1        |
| R8E4000019055                    | CHV-M 400/19,05 | 400      | 19050  | 70/170   | 350 x 1134 x 175 | 64,4        |
| R8E5000019055                    | CHV-M 500/19,05 | 500      | 19050  | 70/170   | 350 x 1244 x 175 | 73,7        |
| R8E6000019055                    | CHV-M 600/19,05 | 600      | 19050  | 70/170   | 350 x 1264 x 200 | 84,1        |
| R8E7500019055                    | CHV-M 750/19,05 | 750      | 19050  | 70/170   | 350 x 1454 x 200 | 104,2       |

Codes R8xxxxxxxxxxx5 cannot have an internal fuse.