



## CHV-M 300/19,05

CHV-M 300/19,05

Code: R8E3000019050 (DESCATALOGADO)

> MV capacitor

### Specifications

#### Isolators

Material	Porcelain
Insulation level	70/170 kV
Pollution level	16 mm / kV

#### Electrical characteristics

Losses (W)	$\leq 0,15$ W / kvar
Power	300 kvar
Discharge resistance	Location: Indoor Discharge time: $\leq 10$ minutes Residual voltage: $\leq 75$ V
Surge	1.1 A 12 h in 24 hours 1.15 A 30 min in 24 hours 1.2 A 5 min in 24 hours 1.30 1 min in 24 hours
Voltage	19050 V

#### Mechanical characteristics

Size (mm) width x height x depth	350 x 1034 x 175 (mm)
Material	Dielectric: Rough polypropylene film Electrode: Laser-cut aluminium foil Impregnating oil: SAS-40E or M/DBT (PCB-free)
Envelope	Stainless steel painted RAL 7035. With 2 wings for fixing to the frame to avoid mechanical stress on the porcelain terminals.
Fastening	Horizontal or vertical
Weight (kg)	56,5

#### Environmental characteristics

Installation, location, position.	Indoor / Outdoor
-----------------------------------	------------------

#### Standards

Standards	IEC 60871-1, IEC 60871-5
-----------	--------------------------



## **CHV-M 300/19,05**

---

Single-phase capacitor (indoor and outdoor use)

Code: R8E3000019050