



CHV-T 750/3,3

CHV-T 750/3,3, Three-phase MV power capacitors

Code: R8K750000330E (CONSULTAR DISPONIBILIDAD)

- > BIL (kV): 20/60
- > Measure: Three-phase
- > Frequency (Hz): 50
- > Q (kvar): 750
- > Un (V): 3300

Specifications

Isolators

Material	Porcelain
Insulation level	20/60 kV
Pollution level	16 mm / kV

Electrical characteristics

Losses (W)	$\leq 0,15$ W / kvar
Power	750 kvar
Discharge resistance	Location: Indoor Discharge time: ≤ 10 minutes Residual voltage: ≤ 75 V
Surge	1.1 A 12 h in 24 hours 1.15 A 30 min in 24 hours 1.2 A 5 min in 24 hours 1.30 1 min in 24 hours
Voltage	3300 V

Mechanical characteristics

Size (mm) width x height x depth	350 x 1252 x 200 (mm)
Material	Dielectric: Rough polypropylene film Electrode: Laser-cut aluminium foil Impregnating oil: SAS-40E or M/DBT (PCB-free)
Envelope	Stainless steel painted RAL 7035. With 2 wings for fixing to the frame to avoid mechanical stress on the porcelain terminals.
Fastening	Horizontal or vertical
Weight (kg)	97,3

Environmental characteristics

Installation, location, position.	Indoor / Outdoor
-----------------------------------	------------------

Standards

Standards	IEC 60871-1, IEC 60871-5
-----------	--------------------------



CHV-T 750/3,3

Three-phase capacitor (indoor and outdoor use)

Code: R8K750000330E

Dimensions

