

URBAN T21

URBAN T21, Outdoor recharge post

Code: V10621. DESCATALOGADO

- > Communications: Ethernet
- > Output type: 400 Vca - 32 A - 22 kW
- > Input current: 35 A
- > Connector type: Type 2 socket
- > Grid type: Three-phase
- > No. Sockets: 1

Description

CIRCUTOR has designed a new range of outdoor charging posts with a new aesthetic design that combines an attractive appearance with safe, reliable and robust construction. Outdoor posts have to be capable of withstanding a wide range of environmental conditions and possible acts of vandalism, while simplifying the installation and maintenance processes for operators. The **URBAN** posts reduce installation time and simplify operations and maintenance tasks.

The **URBAN** devices facilitate charging tasks for all kinds of EV users, incorporating all the electrical protections needed to guarantee safety inside an aluminium metal body. They come with Type-2, mode-3 single-phase or three-phase plugs, depending on the configuration chosen. The **URBAN 10** is designed for locations where simple Plug & Charge operations are required.

Application

URBAN charging posts are especially suited for all types of outdoor parking areas where electric vehicles are parked and charged. Its applications range from public roads and squares, to outdoor car parks at department stores, airport terminals, vehicle sales and rental companies, company employee car parks, etc.



URBAN T21

Outdoor charging posts

Code: V10621.

Specifications

AC power supply

Input intensity	35 A
-----------------	------

Mechanical characteristics

Size (mm) width x height x depth	450 x 1550 x 290 (mm)
----------------------------------	-----------------------

Communication Network

Protocol	OCPP
Technology / Interface	Ethernet 10/100 Base TX (TCP/IP)

Features / performance

Optional	<ul style="list-style-type: none">Anti vandal doors for Type 2 socketsType A earth leakage protection with automatic reclosingType B earth leakage protectionType B earth leakage protection with automatic reclosingSurge protectionLow temperature kit (- 30°C)
----------	--

Type A circuit breaker and earth leakage protection, independent on each connection, LED indicator of the state of charge. Aluminium and ABS plastic casing (IP54 / IK10). Dimensions: 450 x 1550 x 290 mm For 4G communications, see the code table



URBAN T21

Outdoor charging posts

Code: V10621.

Dimensions

