

### **URBAN T21**

URBAN T21, Outdoor recharge post

Code: V10621. DESCATALOGADO

> Communications: Ethernet

> Output type: 400 Vca - 32 A - 22 kW

> Input current: 35 A

Connector type: Type 2 socketGrid type: Three-phase

> No. Sockets: 1

### Description

CIRCUTOR has designed a new range of outdoor charging posts with a new aesthetic design that combines an attractive appearance with safe, reliable and robust construction. Outdoor posts have to be capable of withstanding a wide range of environmental conditions and possible acts of vandalism, while simplifying the installation and maintenance processes for operators. The **URBAN** posts reduce installation time and simplify operations and maintenance tasks.

The **URBAN** devices facilitate charging tasks for all kinds of EV users, incorporating all the electrical protections needed to guarantee safety inside an aluminium metal body. They come with Type-2, mode-3 single-phase or three-phase plugs, depending on the configuration chosen. The **URBAN 10** is designed for locations where simple Plug & Charge operations are required.

#### **Application**

**URBAN** charging posts are especially suited for all types of outdoor parking areas where electric vehicles are parked and charged. Its applications range from public roads and squares, to outdoor car parks at department stores, airport terminals, vehicle sales and rental companies, company employee car parks, etc.









## **URBAN T21**

Outdoor charging posts

Code: V10621.

### **Specifications**

AC power supply	
Input intensity	35 A
Mechanical characteristics	
Size (mm) width x height x depth	450 x 1550 x 290 (mm)
Communication Network	
Protocol	ОСРР
Technology / Type	Ethernet 10/100 Base TX (TCP/IP)
Features / performance	
Optional	<ul> <li>Anti vandal doors for Type 2 sockets</li> <li>Type A earth leakage protection with automatic reclosing</li> <li>Type B earth leakage protection</li> <li>Type B earth leakage protection with automatic reclosing</li> <li>Surge protection</li> <li>Low temperature kit (- 30°C)</li> </ul>

Type A circuit breaker and earth leakage protection, independent on each connection, LED indicator of the state of charge. Aluminium and ABS plastic casing (IP54 / IK10). Dimensions: 450 x 1550 x 290 mm For 4G communications, see the code table



Page 2 of 3





# **URBAN T21**

Outdoor charging posts

Code: V10621.

### **Dimensions**





