



## URBAN T22-C2

---

URBAN T22-C2, Outdoor recharge post

Code: V10626. DESCATALOGADO

- > Communications: Ethernet
- > Output type: 400 Vca - 32 A - 22 kW
- > Input current: 67 A
- > Connector type: Type 2 cable
- > Grid type: Three-phase
- > Charge mode: 3
- > No. Sockets: 2
- > Earth leakage protection: Type A

### Description

---

**URBAN** charging posts have been designed as a robust solution for publicly accessible environments, capable of withstanding a wide range of environmental conditions and possible acts of vandalism, while providing simple installation and maintenance for operators.

**URBAN** devices facilitate charging tasks for all kinds of EV users, incorporating all the electrical protections necessary to guarantee safety inside an aluminium metal body. They can use type 1 and type 2 cables and type 2 plugs and/or Schuko plugs in various combinations, enabling recharging in Mode 1-2 and Mode 3 depending on the configuration chosen.

The **URBAN** series is designed for complex applications where the highest standards of performance are required, with remote management and monitoring or integration into management platforms based on the 1.5 or 1.6 OCPP protocol.

### Application

---

**URBAN** charging posts are especially suitable for all types of outdoor parking. Applications range from public squares, department stores, airports, vehicle sales and rental companies, private car parks, etc.



## URBAN T22-C2

Outdoor charging posts

Code: V10626.

### Specifications

#### AC power supply

Input intensity	67 A
Frequency	50 ... 60 Hz
Type of network	3Ph + N + GND
Nominal voltage	400 V ~ ± 10 %

#### Electrical characteristics

Surge protection (DSP)	Transient surge protector IEC 61643-1 (Class II), (Optional)
Overcurrent protection	PIA 40 A (curve C)
Power balance between charges	1
Cable: Connector type	Type 2 cable
Max. output intensity (A)	32
Charging mode	Mode 3 (IEC 61851-1)
No. of charges	2
Max. output power (kW)	22
Voltage	400 V ~ (± 10 %)

#### Mechanical characteristics

Size (mm) width x height x depth	450 x 1550 x 290 (mm)
Envelope	Aluminum and ABS
Fastening	Floor fixing with 4 bolts
Weight (kg)	55

#### Environmental characteristics

Protection class	IP 54 / IK10
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-20 ... +60 °C
Working temperature	-5 ... +45 °C

#### Communication Network

Protocol	OCPP
Technology / Interface	Ethernet 10/100 Base TX (TCP/IP)

#### User interface

RFID (Radio-Frequency Identification)	ISO/IEC 14443 A/B, MIFARE Classic / Desfire EV1 ISO 18092 / ECMA-340, NFC 13,56 MHz
LED	RGB color charge indicator
Display type	LCD



## URBAN T22-C2

Outdoor charging posts

Code: V10626.

### Standards

Standards	IEC 61851-1, IEC 61851-22, IEC 62196-1, IEC 62196-2, Directiva 2014/35/UE, LVD; 2014/30/UE, EMC
-----------	---

### Features / performance

Energy measurement	MID counter Class 1, UNE-EN 50470-3
Optional	<ul style="list-style-type: none"> <li>• Anti vandal doors for Type 2 sockets</li> <li>• Type A earth leakage protection with automatic reclosing</li> <li>• Type B earth leakage protection</li> <li>• Type B earth leakage protection with automatic reclosing</li> <li>• Surge protection</li> <li>• Low temperature kit (-30°C)</li> <li>• Heating and air conditioning unit (-30 ... +45 °C)</li> </ul>

### Thermal-magnetic protection

Trip curve, Type	MCB (Curva C)
------------------	---------------

### Protection

Safety relay type (class)	RCD Type A (30 mA) RCD Type A (30 mA) with automatic reclosure (optional) RCD Type B (optional) RCD Type B with automatic reclosure (optional)
---------------------------	--

### Output 1

Maximum current	400 Vca - 32 A - 22 kW
Maximum power	400 Vca - 32 A - 22 kW
Voltage range	400 Vca - 32 A - 22 kW
Connector type	Type 2 cable
Network type	Three-phase (AC)

### Output 2

Maximum current	400 Vca - 32 A - 22 kW
Maximum power	400 Vca - 32 A - 22 kW
Voltage range	400 Vca - 32 A - 22 kW
Connector type	Type 2 cable
Network type	Three-phase (AC)

### URBAN 20

URBAN 20 outdoor charging post

CODE	TYPE	No. Sockets	Output type	Connector type	Grid type
URBAN 20					
V1062C.	URBAN T22-C2 63	1	400 Vca - 63 A - 43 kW	Type 2 cable	Three-phase

Independent, earth leakage protection and circuit breaker protection per plug, MID Integrated energy measurement, RFID reader for identification and charging activation. Data storage, Ethernet communications, 4G communications (optional), OCPP 1.5/1.6 communications protocol, Weight: 55 kg, IP54-IP65 aluminium housing, dimensions 1550x450x290 mm. 4-m cable length (depending on model).



## URBAN T22-C2

Outdoor charging posts

Code: V10626.

### Dimensions

