



URBAN SLAVE M2-C2

Code: V1064A. DESCATALOGADO

Description

The **URBAN MASTER/SLAVE** devices have been designed to minimise the initial investment and maintenance costs when several chargers are required. This solution consists of a combination of a **Master** charger that controls a set of **Slave** chargers.

The system as a whole works as if all the chargers were smart, either by connecting the Master to a manager via OCPP or independently by setting up a white list of users for the group. A maximum power limit for the whole group can also be specified, thus saving on the installation and power costs.

Application

Designed for private facilities such as businesses or residential developments with a single administrator, it also offers an appealing solution for public facilities such as shopping centres, car parks, airports and more.



URBAN SLAVE M2-C2

Outdoor charging posts with Master-Slave system

Code: V1064A.

Specifications

Mechanical characteristics

| | |
|----------------------------------|-----------------------|
| Size (mm) width x height x depth | 450 x 1550 x 290 (mm) |
| Weight (kg) | 55 |

Communication Network

| | |
|------------------------|----------------------------------|
| Protocol | OCPP |
| Technology / Interface | Ethernet 10/100 Base TX (TCP/IP) |

URBAN MASTER/SLAVE

Intelligent Master/Slave charging posts

| CODE | TYPE | No. Sockets | Output type | Connector type | Grid type |
|---------------------|--------------------|-------------|-------------------------|----------------|--------------|
| URBAN MASTER | | | | | |
| V10632. | URBAN MASTER M2 | 2 | 230 Vca - 32 A - 7,4 kW | Type 2 socket | Single-phase |
| V10633. | URBAN MASTER T2 | 2 | 400 Vca - 32 A - 22 kW | Type 2 socket | Three-phase |
| V10636. | URBAN MASTER T2-C2 | 2 | 400 Vca - 32 A - 22 kW | Type 2 cable | Three-phase |
| URBAN SLAVE | | | | | |
| V10642. | URBAN SLAVE M2 | 2 | 230 Vca - 32 A - 7,4 kW | Type 2 socket | Single-phase |
| V10643. | URBAN SLAVE T2 | 2 | 400 Vca - 32 A - 22 kW | Type 2 socket | Three-phase |
| V10646. | URBAN SLAVE T2-C2 | 2 | 400 Vca - 32 A - 22 kW | Type 2 cable | Three-phase |

System with up to 6 Slave chargers per Master depending on the optional switch chosen. 8" vandal-proof TFT touch screen, independent overcurrent and earth leakage 30-mA, type-B protection per plug, integrated MID-certified energy measurement, RFID reader for authentication and charge activation - ISO 14443 A/B, data storage, Ethernet communications, 4G communications (optional), OCPP 1.5/1.6 communications protocol, Weight: 30 kg, IP54-IK10 aluminium housing, dimensions 1550x450x290 mm. 4-m cable length (depending on model).



URBAN SLAVE M2-C2

Outdoor charging posts with Master-Slave system

Code: V1064A.

Dimensions

