



URBAN SLAVE CCS2

URBAN SLAVE CCS2, DC recharging post

Code: V10740. DESCATALOGADO

> Communications: Ethernet UTP

> Output type: 150 ... 920 Vcc - 70 A - 25 kW

> Connector type: CCS Combo 2 [FF]

> Grid type: Three-phase > Charge mode: 4 > No. Sockets: 1

> Earth leakage protection: Type B

Description

The URBAN MASTER/SLAVE CCS solution consists of a combination of a smart Master charger that provides communications and has an RFID reader, 8" touchscreen and an optional bank card payment system that controls a set of Slaves.

With a compact and robust design and an aluminium enclosure for all types of environments, the Urban CCS is the fast-charging version of Circutor's venerable Urban line, with a DC charging power of 25 kW, thus sidestepping the power limitation imposed by chargers on board electric vehicles with AC charging.

The system as a whole works as if all the chargers were smart, either by connecting the Master to a manager via OCPP, or independently by setting up a white list of users for the group.

Application

The Urban CCS range has been developed to offer a fast-charging solution in environments where there is no high-power electrical infrastructure, and where AC charging is insufficient. It is ideal for charging small fleets

vehicles, dealerships, carsharing companies, small private car parks, etc., without making a major investment. This device can be installed on the wall or floor thanks to its two models (wallbox and post).







URBAN SLAVE CCS2

Outdoor charging posts

Code: V10740.

Specifications

AC power supply		
Input intensity	39 A	
Power factor	> 0,98	
Frequency	/ 60 Hz	
Type of network	3Ph + N + GND	
Nominal voltage	$400~V\sim(\pm~10~\%)$ (480 V \sim bajo demanda)	
Electrical characteristics		
Surge protection (DSP)	Optional	
Overcurrent protection	MCB curve C (50 A)	
Cable: Connector type	CCS Combo 2 (5.5-m cable length)	
Max. output intensity (A)	0 70 cc	
Charging mode	Mode 4	
No. of charges	1	
Max. output power (kW)	25 (cc)	
Efficiency	94%	
Voltage	150 920 Vdc	
Mechanical characteristics		
Size (mm) width x height x depth	479 x 1750 x 288 (mm)	
Envelope	Aluminium & ABS	
Noise	< 55 dB	
Weight (kg)	55	
Environmental characteristics		
Protection class	IP 54 / IK10	
Relative humidity (without condensation)	5 95 %	
Storage temperature	-40 +60 °C	
Working temperature	-35 +45 °C	
Standards		
Certifications	CE	
Electrical safety, Installation category	CAT III 300 V	
Standards	IEC 61851-1, IEC 61851-23, IEC 61851-21-2, CE / Combo, DIN 70121, ISO 15118, MID Class 1 - EN 50470-3	
Communication Network		



Page 2 of 3





URBAN SLAVE CCS2

Outdoor charging posts

Code: V10740.

Electrical safety

Insulation	Double-insulated electric shock protection class II (IEC 61010)
User interface	
LED	RGB color charge indicator
Features / performance	
Heating and air conditioning unit	-35 +45 °C (Opcional)
Energy measurement	Meter for measuring alternating electrical energy according to UNE-EN 50470
Protection	
Safety relay type (class)	RCD B
Output 1	
Maximum current	70 A
Maximum power	25 kW
Voltage range	150-920 Vcc
Connector type	CCS Combo 2 (FF)
Network type	DC

URBAN MASTER DC

Intelligent charging posts, DC charging

CODE	TYPE	No. Sockets	Output type	Connector type	Grid type
MASTER					
V10730.	URBAN MASTER CCS2	1	150 920 Vcc - 70 A - 25 kW	CCS Combo 2 [FF]	Three-phase

