



## URBAN SLAVE CCS2

URBAN SLAVE CCS2, DC recharging post

Code: V10740. DESCATALOGADO

- > Communications: Ethernet UTP
- > Output type: 150 ... 920 Vcc - 70 A - 25 kW
- > Connector type: CCS Combo 2 [FF]
- > Grid type: Three-phase
- > Charge mode: 4
- > No. Sockets: 1
- > Earth leakage protection: Type B

### Description

The URBAN MASTER/SLAVE CCS solution consists of a combination of a smart Master charger that provides communications and has an RFID reader, 8" touchscreen and an optional bank card payment system that controls a set of Slaves.

With a compact and robust design and an aluminium enclosure for all types of environments, the Urban CCS is the fast-charging version of Circutor's venerable Urban line, with a DC charging power of 25 kW, thus sidestepping the power limitation imposed by chargers on board electric vehicles with AC charging.

The system as a whole works as if all the chargers were smart, either by connecting the Master to a manager via OCPP, or independently by setting up a white list of users for the group.

### Application

The Urban CCS range has been developed to offer a fast-charging solution in environments where there is no high-power electrical infrastructure, and where AC charging is insufficient. It is ideal for charging small fleets of electric vehicles, dealerships, carsharing companies, small private car parks, etc., without making a major investment. This device can be installed on the wall or floor thanks to its two models (wallbox and post).



## URBAN SLAVE CCS2

Outdoor charging posts

Code: V10740.

### Specifications

#### AC power supply

Input intensity	39 A
Power factor	> 0,98
Frequency	50 / 60 Hz
Type of network	3Ph + N + GND
Nominal voltage	400 V ~ (± 10 %) (480 V ~ bajo demanda)

#### Electrical characteristics

Surge protection (DSP)	Optional
Overcurrent protection	MCB curve C (50 A)
Cable: Connector type	CCS Combo 2 (5.5-m cable length)
Max. output intensity (A)	0 ... 70 cc
Charging mode	Mode 4
No. of charges	1
Max. output power (kW)	25 (cc)
Efficiency	94%
Voltage	150 ... 920 Vdc

#### Mechanical characteristics

Size (mm) width x height x depth	479 x 1750 x 288 (mm)
Envelope	Aluminium & ABS
Noise	< 55 dB
Weight (kg)	55

#### Environmental characteristics

Protection class	IP 54 / IK10
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-40 ... +60 °C
Working temperature	-35 ... +45 °C

#### Standards

Certifications	CE
Electrical safety, Installation category	CAT III 300 V
Standards	IEC 61851-1, IEC 61851-23, IEC 61851-21-2, CE / Combo, DIN 70121, ISO 15118, MID: Class 1 - EN 50470-3

#### Communication Network

Technology / Interface	Ethernet 10/100 Base TX (TCP/IP)
------------------------	----------------------------------



## URBAN SLAVE CCS2

Outdoor charging posts

Code: V10740.

### Electrical safety

Insulation

Double-insulated electric shock protection class II (IEC 61010)

### User interface

LED

RGB color charge indicator

### Features / performance

Heating and air conditioning unit

-35 ... +45 °C (Optional)

Energy measurement

Meter for measuring alternating electrical energy according to UNE-EN 50470

### Protection

Safety relay type (class)

RCD B

### Output 1

Maximum current

70 A

Maximum power

25 kW

Voltage range

150-920 Vcc

Connector type

CCS Combo 2 (FF)

Network type

DC

### URBAN MASTER DC

Intelligent charging posts, DC charging

CODE	TYPE	No. Sockets	Output type	Connector type	Grid type
<b>MASTER</b>					
V10730.	URBAN MASTER CCS2	1	150 ... 920 Vcc - 70 A - 25 kW	CCS Combo 2 [FF]	Three-phase