



RAPTION 50 CCS2 CHA T2C63

RAPTION 50 CCS2 CHA T2C63, Outdoor recharge station

Code: V17131. **DESCATALOGADO**

- > Communications: Ethernet | 4G
- > Output type: 50-500 Vcc - 125 A - 50 kW | 400 Vca - 63 A - 43 kW
- > Connector type: CCS Combo 2 (FF) | JEVS G105 - CHAdeMO (AA) | Type 2 cable
- > Grid type: Three-phase
- > Charge mode: 3 | 4
- > No. Sockets: 3

Description

Fast charging device with CHAdeMO and COMBO CCS connectors for DC charging in Mode 4, and with Type 1 or Type 2 connectors for AC charging in Mode 3. The fast-charging **RAPTION 50** device allows opportunity charging in cases where charging speed is required. Depending on the capacity of the batteries, it can provide a full or partial charge in a short time.

The **RAPTION 50** station works with power levels of up to 50 kW. The unit has an interactive screen for easy user interaction, and communications capabilities (Ethernet, 4G) for remote management from the control centre.

Application

RAPTION devices are ideal for public charging, shopping centres, rental companies, vehicle fleets, company car parks, etc.



RAPTION 50 CCS2 CHA T2C63

Quick outdoor charging station

Code: V17131.

Specifications

AC power supply

| | |
|-----------------|---|
| Consumption | 38 W en reposo |
| Input intensity | 138 A |
| Efficiency | 95% |
| Power factor | > 0,98 |
| Frequency | 50 / 60 Hz |
| Type of network | 3Ph + N + GND |
| Nominal voltage | 400 V ~ ($\pm 10\%$) (480 V ~ bajo demanda) |

Electrical characteristics

| | |
|---------------------------|---|
| Surge protection (DSP) | Optional |
| Overcurrent protection | Optional |
| Cable: Connector type | CCS Combo 2 JEVS G105 - CHAdeMO; Cable Type 2 (Cable length 3m) |
| Max. output intensity (A) | 0 ... 125 cc / 63 ~ |
| Charging mode | Mode 3, 4 |
| No. of charges | 3 |
| Max. output power (kW) | 50 (CC) / 44 (~) |
| Voltage | 50 ... 500 Vdc / 400 V~ |

Mechanical characteristics

| | |
|----------------------------------|-----------------------|
| Size (mm) width x height x depth | 940 x 1800 x 520 (mm) |
| Envelope | Stainless steel |
| Weight (kg) | 280 |

Environmental characteristics

| | |
|--|----------------|
| Protection class | IP 54 / IK10 |
| Relative humidity (without condensation) | 5 ... 95 % |
| Storage temperature | -20 ... +60 °C |
| Working temperature | -30 ... +45 °C |

Standards

| | |
|--|---|
| Certifications | CE |
| Electrical safety, Installation category | CAT III 300 V |
| Standards | IEC 61851-1, IEC 61851-22, IEC 61851-23, IEC 62196-1, IEC 62196-2, IEC 62196-3, CHAdeMO Certified, CCS (DIN 70121, ISO 15118) |

Communication Network

| | |
|-------------------|----------------------------------|
| Protocol | OCPP |
| Technology / Type | Ethernet 10/100 Base TX (TCP/IP) |



RAPTION 50 CCS2 CHA T2C63

Quick outdoor charging station

Code: V17131.

User interface

| | |
|---------------------------------------|---|
| RFID (Radio-Frequency Identification) | ISO/IEC 14443 A/B, MIFARE Classic / Desfire EV1 ISO 18092 / ECMA-340, NFC 13,56 MHz |
| LED | RGB color charge indicator |
| Display type | 8" Touch TFT, multilingual |

Features / performance

| | |
|-----------------------------------|---|
| Heating and air conditioning unit | -30 ... +45 °C (Optional) |
| Energy measurement | Meter for measuring alternating electrical energy according to UNE-EN 50470 |

Protection

| | |
|---------------------------|----------------|
| Safety relay type (class) | RCD (optional) |
|---------------------------|----------------|

Radio communication

| | |
|-------------------|-----------------------|
| Technology / Type | 4G / GPRS / GSM Modem |
|-------------------|-----------------------|

Output 1

| | |
|-----------------|------------------|
| Maximum current | 125 A |
| Maximum power | 50 kW |
| Voltage range | 50-500 Vcc |
| Connector type | CCS Combo 2 (FF) |
| Network type | Three-phase (DC) |

Output 2

| | |
|-----------------|--------------------------|
| Maximum current | 125 A |
| Maximum power | 50 kW |
| Voltage range | 50-500 Vcc |
| Connector type | JEVS G105 - CHAdeMO (AA) |
| Network type | Three-phase (DC) |

Output 3

| | |
|-----------------|------------------|
| Maximum current | 63 A |
| Maximum power | 43 kW |
| Voltage range | 400 Vca |
| Connector type | Type 2 cable |
| Network type | Three-phase (AC) |

8" vandal-proof TFT touch screen, independent overcurrent and earth leakage 30-mA, type-B protection per plug, integrated MID-certified energy measurement, RFID reader for authentication and charge activation - ISO 14443 A/B, data storage, Ethernet communications, 4G communications, OCPP 1.5/1.6 communications protocol, Weight: 230 kg, suitable for wall mounting, stainless steel IP54 - IK10 enclosure, dimensions: 350x940x1800 mm. 3-m cable length (5 m optional).



RAPTION 50 CCS2 CHA T2C63

Quick outdoor charging station

Code: V17131.

Dimensions

