



RAPTION 100 CCS1, Outdoor recharge station

Code: V17311.

> Communications: Ethernet | 4G

> Output type: 150-920 Vcc - 250 A - 100 kW

> Connector type: CCS Combo 1 (CC)

> Grid type: Three-phase > Charge mode: 4 > No. Sockets: 1

Description

Fast charging device with CHAdeMO and COMBO CCS connectors for DC charging in Mode 4, and with Type 1 or Type 2 connectors for AC charging in Mode 3. The Raption 100 quick charging units allow vehicles to be charged on the go when quick recharging is required. Depending on the capacity of the batteries, it can provide a full or partial charge in a short time.

Application

RAPTION devices are ideal for public charging, shopping centres, rental companies, vehicle fleets, company car parks, etc.



Page 1 of 4





Quick outdoor charging station

Code: V17311.

Specifications

AC power supply			
Input intensity	160 A		
Power factor	> 0,98		
Frequency	50 / 60 Hz		
Type of network	3Ph + N + GND		
Nominal voltage	400 V \sim (± 10 %) (480 V \sim bajo demanda)		
Electrical characteristics			
Overcurrent protection	Circuit breaker		
Cable: Connector type	CCS Combo 1 (CC)		
Max. output intensity (A)	DC: 250		
Charging mode	Mode 4		
No. of charges	1		
Max. output power (kW)	DC: 100		
Efficiency	95%		
Voltage	150 920 Vdc		
Mechanical characteristics			
Size (mm) width x height x depth	940 x 1800 x 520 (mm)		
Envelope	Stainless steel		
Noise	< 55 dB		
Environmental characteristics			
Protection class	IP 54 / IK10		
Relative humidity (without condensation)	5 95 %		
Storage temperature	-40 +60 °C		
Working temperature	-10 +50 °C		
Standards			
Certifications	IEC 61851-1; IEC 61851-23; IEC 61851-21-2; CCS (DIN 70121; ISO 15118)		
Electrical safety, Installation category	CAT III 300 V		
Standards	IEC 61851-1; IEC 61851-23; IEC 61851-21-2; CCS (DIN 70121; ISO 15118)		
Communication Network			
Protocol	ОСРР		
Technology / Interface	Ethernet 10/100 Base TX (TCP/IP)		
User interface			
RFID (Radio-Frequency Identification)	ISO / IEC 14443A / B, MIFARE Classic, MIFARE DESFire, MIFARE, DESFire EV1, ISO		







Quick outdoor charging station

Code: V17311.

	18092 / ECMA-340 (NFC) 13.56 MHz		
LED	RGB color charge indicator		
Display type	8" TFT touch screen anti-vandalism display		
Features / performance			
Optional	4-pole transient overvoltages (IEC 61643-11 Class II)		
	Self-resetting residual current circuit breaker type B		
	Heater∕heater for -30 +50 °C		
	Vandal protection: mechanical locking of the connector		
	Contactless payment system		
Protection			
Safety relay type (class)	Туре В		
Radio communication			
Technology / Type	4G / GPRS / GSM Modem		
Output 1			
Maximum current	125 A		
Maximum power	50 kW		
Voltage range	50-500 Vcc		
Connector type	CCS Combo 1 (CC)		
Network type	Three-phase (DC)		

RAPTION 100

Compact ultra-fast recharging stations

CODE	TYPE	No. Sockets	Output type	Connector type	Grid type
V17311.	RAPTION 100 CCS1	1	150-920 Vcc - 250 A - 100 kW	CCS Combo 1 (CC)	Three-phase
V1732D.	RAPTION 100 CCS1 CHA	2	150-920 Vcc - 250 A - 100 kW 50-400 Vcc - 125 A - 50 kW	CCS Combo 1 (CC) JEVS G105 - CHAdeMO (AA)	Three-phase
V1732C.	RAPTION 100 CCS1 T1C32	2	150-920 Vcc - 250 A - 100 kW 400 Vca - 32 A - 22 kW	CCS Combo 1 (CC) Type 1 cable	Three-phase
V1732B.	RAPTION 100 CCS1 T2S32	2	150-920 Vcc - 250 A - 100 kW 400 Vca - 32 A - 22 kW	CCS Combo 1 (CC) Type 2 socket	Three-phase
V17337.	RAPTION 100 CCS1 CHA T2S32	3	150-920 Vcc - 200/250 A - 100 kW 50-400 Vcc - 125 A - 50 kW 400 Vca - 32 A - 22 kW	CCS Combo 1 (CC) JEVS G105 - CHAdeMO (AA) Type 2 socket	Three-phase
V17338.	RAPTION 100 CCS1 CHA T1C32	3	150-920 Vcc - 200/250 A - 100 kW 50-400 Vcc - 125 A - 50 kW 400 Vca - 32 A - 22 kW	CCS Combo 1 (CC) JEVS G105 - CHAdeMO (AA) Type 1 cable	Three-phase

8" vandal-proof TFT touch screen, independent overcurrent and earth leakage 30-mA, type-B protection per plug, integrated MID-certified energy measurement, RFID reader for authentication and charge activation - ISO 14443 A/B, data storage, Ethernet communications, 4G communications, OCPP 1.6J/2.0 (ready) communications protocol, Weight: 255 kg, suitable for wall mounting, stainless steel IP54 - IK10 enclosure, dimensions: 350x940x1800 mm. 3-m cable length (5 m optional).



Page 3 of 4





Quick outdoor charging station

Code: V17311.

Dimensions



