



## RAPTION 50 EVO CCS1 CHA T2S32

RAPTION 50 EVO CCS1 CHA T2S32, Outdoor recharge station

Code: V17437.

- > Communications: Ethernet | 4G
- > Output type: 100-920 Vcc - 125 A - 50 kW| 400 Vca - 32 A - 22 kW
- > Connector type: CCS Combo 1 (CC)| JEVS G105 - CHAdeMO (AA)| Type 2 socket
- > Grid type: Three-phase
- > Charge mode: 3 | 4
- > No. Sockets: 3

### Description

Fast-charging device with CHAdeMO and COMBO CCS connectors for DC charging in Mode 4, and with Type 1 or Type 2 connectors for AC charging in Mode 3. The **RAPTION 50 EVO** device is perfect in situations where fast charging is required. Depending on the capacity of the batteries, it can provide a full or partial charge in a short time.

The **RAPTION 50 EVO** station works with power levels of up to 50 kW, though it can be expanded to 100 kW. The unit has an interactive screen for easy user interaction, and communications capabilities (Ethernet, 4G) for remote management from the control centre.

### Application

**RAPTION** devices are ideal for public charging, shopping centres, rental companies, vehicle fleets, company car parks, etc.



## RAPTION 50 EVO CCS1 CHA T2S32

Quick outdoor charging station

Code: V17437.

### Specifications

#### AC power supply

Input intensity	108 A
Efficiency	95 % con potencia nominal de salida
Power factor	> 0,98
Frequency	50 / 60 Hz
Type of network	3Ph + N + GND
Nominal voltage	400 V ~ ( $\pm 10$ %) (480 V ~ bajo demanda)

#### Electrical characteristics

Surge protection (DSP)	Optional
Overcurrent protection	Optional
Cable: Connector type	CCS Combo 1 JEVS G105 - CHAdeMO (Cable length 3m)Type 2 socket
Max. output intensity (A)	0 ... 125 cc / 32 ~
Charging mode	Mode 3, 4
No. of charges	3
Max. output power (kW)	50 (CC) / 22 (~)
Voltage	50 ... 500 Vdc / 400 V~

#### Mechanical characteristics

Size (mm) width x height x depth	940 x 1800 x 520 (mm)
Envelope	Stainless steel
Noise	< 55 dB
Weight (kg)	230

#### Environmental characteristics

Protection class	IP 54 / IK10
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-20 ... +60 °C
Working temperature	-30 ... +45 °C

#### Standards

Certifications	CE
Electrical safety, Installation category	CAT III 300 V
Standards	IEC 61851-1, IEC 61851-22, IEC 61851-23, IEC 62196-1, IEC 62196-2, IEC 62196-3, CHAdeMO Certified, CCS (DIN 70121, ISO 15118)

#### Communications

Protocol	Ocpp
Type	Ethernet 10/100 Base TX (TCP/IP)



## RAPTION 50 EVO CCS1 CHA T2S32

Quick outdoor charging station

Code: V17437.

Speed	4G / GPRS / GSM Modem
<b>Electrical safety</b>	
Insulation	Double-insulated electric shock protection class II (IEC 61010)
<b>User interface</b>	
RFID (Radio-Frequency Identification)	ISO/IEC 14443 A/B, MIFARE Classic / Desfire EV1 ISO 18092 / ECMA-340, NFC 13,56 MHz
LED	RGB color charge indicator
Display type	8" Touch TFT, multilingual
<b>Features / performance</b>	
Heating and air conditioning unit	-30 ... +45 °C (Optional)
Energy measurement	Meter for measuring alternating electrical energy according to UNE-EN 50470
<b>Protection</b>	
Safety relay type (class)	RCD (optional)
<b>Output 1</b>	
Maximum current	125 A
Maximum power	50 kW
Voltage range	50-500 Vcc
Connector type	CCS Combo 1 (CC)
Network type	Three-phase (DC)
<b>Output 2</b>	
Maximum current	125 A
Maximum power	50 kW
Voltage range	50-500 Vcc
Connector type	JEVS G105 - CHAdeMO (AA)
Network type	Three-phase (DC)
<b>Output 3</b>	
Maximum current	32 A
Maximum power	22 kW
Voltage range	400 Vca
Connector type	Type 2 socket
Network type	Three-phase (AC)

### RAPTION 50 EVO

Compact fast charging stations expandable to 100 kW



## RAPTION 50 EVO CCS1 CHA T2S32

Quick outdoor charging station

Code: V17437.

CODE	TYPE	No. Sockets	Output type	Connector type	Grid type
V17410.	RAPTION 50 EVO CCS2	1	100-920 Vcc - 125 A - 50 kW	CCS Combo 2 (FF)	Three-phase
V17411.	RAPTION 50 EVO CCS1	1	100-920 Vcc - 125 A - 50 kW	CCS Combo 1 (CC)	Three-phase
V17422.	RAPTION 50 EVO CCS2 T2C32	2	100-920 Vcc - 125 A - 50 kW  400 Vca - 32 A - 22 kW	CCS Combo 2 (FF)  Type 2 cable	Three-phase
V17423.	RAPTION 50 EVO CCS2 T2S32	2	100-920 Vcc - 125 A - 50 kW  400 Vca - 32 A - 22 kW	CCS Combo 2 (FF)   Type 2 socket	Three-phase
V1742B.	RAPTION 50 EVO CCS1 T2S32	2	100-920 Vcc - 125 A - 50 kW  400 Vca - 32 A - 22 kW	CCS Combo 1 (CC)   Type 2 socket	Three-phase
V1742C.	RAPTION 50 EVO CCS1 T1C32	2	100-920 Vcc - 125 A - 50 kW  400 Vca - 32 A - 22 kW	CCS Combo 1 (CC)  Type 1 cable	Three-phase
V1742D.	RAPTION 50 EVO CCS1 CHA	2	100-920 Vcc - 125 A - 50 kW	CCS Combo 1 (CC)  JEVS G105 - CHAdeMO (AA)	Three-phase
V17430.	RAPTION 50 EVO CCS2 CHA T2S32	3	100-920 Vcc - 125 A - 50 kW  400 Vca - 32 A - 22 kW	CCS Combo 2 (FF)  JEVS G105 - CHAdeMO (AA)  Type 2 socket	Three-phase
V17432.	RAPTION 50 EVO CCS2 CHA T2C32	3	100-920 Vcc - 125 A - 50 kW  400 Vca - 32 A - 22 kW	CCS Combo 2 (FF)  JEVS G105 - CHAdeMO (AA)  Type 2 cable	Three-phase
V17437.	RAPTION 50 EVO CCS1 CHA T2S32	3	100-920 Vcc - 125 A - 50 kW  400 Vca - 32 A - 22 kW	CCS Combo 1 (CC)  JEVS G105 - CHAdeMO (AA)  Type 2 socket	Three-phase
V17438.	RAPTION 50 EVO CCS1 CHA T1C32	3	100-920 Vcc - 125 A - 50 kW  400 Vca - 32 A - 22 kW	CCS Combo 1 (CC)  JEVS G105 - CHAdeMO (AA)  Type 1 cable	Three-phase

Expandable to 100 kW, 8" vandal-proof TFT touch screen, independent overcurrent and earth leakage 30-mA, type-B protection per plug, integrated MID-certified energy measurement, RFID reader for authentication and charge activation - ISO 14443 A/B, data storage, Ethernet communications, 4G communications, OCPP 1.5/1.6 communications protocol, Weight: 230 kg, suitable for wall mounting, stainless steel IP54 - IK10 enclosure, dimensions: 350x940x1800 mm. 3-m cable length (5 m optional).



## RAPTION 50 EVO CCS1 CHA T2S32

Quick outdoor charging station

Code: V17437.

### Dimensions

